

DISPLAY DEVICES

Design • Engineering • Manufacturing

DEALER PRICES March, 2010

Camera Accessories.....	<u>3</u>
Flat Panel Monitor Accessories.....	<u>3</u>
Carts.....	<u>3</u>
Ceiling Mounts- Lower Components.....	<u>4</u>
Ceiling Mounts- Middle Components.....	<u>4</u>
Ceiling Mounts- Upper Components.....	<u>5</u>
Ceiling Mounts-Rotating.....	<u>5</u>
Enclosure- Indoor & Protective Bezels.....	<u>7</u>
Enclosure- Outdoor.....	<u>9</u>
Enclosures- Options.....	<u>10</u>
Lifts.....	<u>12</u>
Lifts Options.....	<u>14</u>
Specialty Mounts.....	<u>14</u>
Wall Mounts.....	<u>15</u>
Wall Mounts- Articulating.....	<u>16</u>
Wall Mounts- VESA 75-100.....	<u>16</u>
Vogels Ceiling Mounts- Flat Panel.....	<u>16</u>
Vogels Floor Stands- Flat Panel.....	<u>17</u>
Vogels Wall Mounts- Flat Panel.....	<u>17</u>
Vogels Wall Mounts- Flat Panel-Articulating.....	<u>17</u>
Media Servers.....	<u>18</u>
Microphone Accessories.....	<u>18</u>
Pan Tilts.....	<u>20</u>
Controllers.....	<u>20</u>
Heads & Head Accessories.....	<u>20</u>
Mounts.....	<u>21</u>
Power Supplies.....	<u>22</u>
Control & Environmental Accessories.....	<u>22</u>
Projector Accessories.....	<u>23</u>
Ceiling Mounts- Anti Theft.....	<u>23</u>
Ceiling Mounts- Rotating.....	<u>23</u>
Ceiling Mounts-Traditional- Lower Components.....	<u>24</u>
Ceiling Mounts-Traditional- Middle Components.....	<u>25</u>
Ceiling Mounts-Traditional- Upper Components.....	<u>26</u>
Enclosure- Outdoor.....	<u>28</u>

Enclosure- Sound.....	28
Lens Shutter.....	31
Lifts IBL Series Projector Lifts (35 # capacity).....	32
Lifts UpLift USD Series (40 # Capacity).....	32
Lifts Data Lite LCD Series (80 # capacity).....	32
Lifts DataLift DL3B Series (160 # capacity).....	34
Lifts DataWide DL3W Series (400 # capacity).....	36
Lifts Motorized Rotation Options.....	38
Lifts Options.....	38
Stackers.....	41
Vogels Ceiling Mounts- Projector.....	42
Pump Toppers.....	43
Specialized Connectors.....	43
Ultra Bright & High Bright LCD Monitors.....	44
24".....	44
32".....	45
40".....	46
46".....	47
52".....	48
57".....	50
65".....	51
70".....	52
Wall Plates & Rack Panels.....	54
Blank Rack Panels & Accessories.....	54
Custom Wall Plates & Rack Panels.....	54
Stock Wall Plates.....	55
Wolfvision Accessories.....	60

Display Devices, Inc.
5880 North Sheridan Blvd.
Arvada, CO. 80003 USA

Phone: 303-412-0399
Fax: 303-412-9346
www.DisplayDevices.com
sales@DisplayDevices.com

Possession of a Dealer Price List does not constitute an Authorized Dealer
relationship with Display Devices, Inc.

Model #	Motorized Ceiling Camera Lift	List
CCL-2855	Teleconference Camera Ceiling Lift 28" retracted height, 31" maximum travel distance. Includes standard 3-button handheld wired remote for programming and dry contact closure interface. Includes ceiling closure system and plenum housing. 20 lb weight capacity. 110V. Camera dimensions not to exceed 16.5" W X 7.75"D** X 16" H (** The length can be a bit longer depending on if part of the base can fit under the back overhang).	\$4,550.00
CCL-2855 220V	Teleconference Camera Ceiling Lift 28" retracted height, 31" maximum travel distance. Includes standard 3-button handheld wired remote for programming and dry contact closure interface. Includes ceiling closure system and plenum housing. 20 lb weight capacity. 220V. Camera dimensions not to exceed 6.18"H x 10.87"W x 5.27"D.	\$4,550.00
CamPan	Camera Mount Panel for mounting light-weight camera/pan/tilt on PLMT series pole mounts. Provides tilt adjustment, 20 lb. capacity. Specify make & model of camera system.	\$215.00
Flat Panel Monitor		
Model #	Flat Panel Monitor Carts	List
PDC-1	PlasmaCart. Mobile Cart for Plasma Displays. Ultra sturdy pyramid design for all flat panel displays. 12" vertical adjustment. Requires PM-### to mount plasma display. Optional signal prewire.	\$970.00
OPT11-PDC	PlasmaCart Prewire 1- RGBHV, 1- HDMI, 1- stereo audio pair of cables. Call for other requirements.	\$130.00
PDC-2	PlasmaCart - Dual Mount. Mobile Cart for Plasma Displays. Ultra sturdy pyramid design for all flat panel displays. For mounting two flat panel displays stacked in landscape mode. 12" vertical adjustment. Requires two PM-### to mount plasma displays. Optional signal prewire.	\$1,250.00
OPT11-PDC2	PlasmaCart Prewire dual 2- RGBHV, 2- HDMI, 2- stereo audio pair of cables. Call for other requirements.	\$260.00
CMC-5000	Confidence Monitor Cart - Standard. Low profile mobile cart for teleprompting and speaker confidence monitors. Lightweight black powder coated aluminum frame with locking casters. Adjustable height. For 30" - 50" monitors. Includes Universal Flat Panel Mount - fits most displays.	\$800.00
CMC-2500	Confidence Monitor Cart - Mini. Low profile mobile cart for teleprompting and speaker confidence monitors. Lightweight black powder coated aluminum frame with locking casters. Adjustable height. For 19" - 27" monitors. Includes fixed VESA 100x100 & 200x200 mount plate - fits most displays.	\$750.00

Model #	Flat Panel Display Ceiling Mounts- Lower Components	List
SPD-###	Single Panel Display Pole Mount assembly. Provides threaded collar for 2" pole with +/-15° tilt and includes flat panel mount. Landscape or Portrait mode. Specify display panel make and model. Anything that is lower than a 100 x 200 vesa pattern use 118-044/ 100 x 200 or larger use 65-349 w/ adapter plate.	\$390.00
DPD-###	Dual Panel Display Pole Mount assembly. Provides threaded collar for 2" pole with +/-15° tilt and includes (2) panel mounts. Landscape or Portrait mode. Specify display panel make and model.	\$635.00
Model #	Flat Panel Display Ceiling Mounts- Middle Components	List
2-15	2" to 1.5" reducer - allows DDI mounts to use a 1.5" pole (1.5" female to 2" male threads).	\$50.00
15-2	1.5" to 2" collar - allows PLMT-T / AA / U / C / CTP2X2 to be used with 1.5" poles (2" female to 1.5" male threads)	\$50.00
CTR-2-W	Ceiling Trim Ring Magnetic escutcheon ring for 2" pole. White finish.	\$25.00
CTR-2-B	Ceiling Trim Ring Magnetic escutcheon ring for 2" pole. Black finish.	\$25.00
CTR-2-P	Ceiling Trim Ring Magnetic escutcheon ring for 2" pole. Primer finish.	\$25.00
PLMT-PP1	Pole Mount PowerPRO Provides Single 1G junction box on threaded collar for 2" pole. Includes 1) J-box with threaded conduit connection points for plenum applications.	\$199.00
PLMT-PP2	Pole Mount PowerPRO Provides Dual 1G junction box on threaded collar for 2" pole. Includes 2 J-boxes; one duplex for 110V AC power and one empty for signal connection.	\$199.00
PLMT-A(x)	Pole Mount Adjustable Pole 2 inch diameter, adjustable length. Specify (x) length: (1)1-2', (2)2-4', or (3)3-6'.	\$115.00
PLMT-A1	Pole Mount Adjustable Pole 2 inch diameter, adjustable length of 1' to 2'.	\$115.00
PLMT-A2	Pole Mount Adjustable Pole 2 inch diameter, adjustable length of 2' to 4'.	\$115.00
PLMT-A3	Pole Mount Adjustable Pole 2 inch diameter, adjustable length of 3' to 6'.	\$115.00
PLMT-A4	Pole Mount Adjustable Pole 2 inch diameter, adjustable length of 4' to 8'.	\$165.00
PL-2.0-06	Six Inch Pole 2" diameter x 6" long.	\$26.00
PL-2.0 - SPEC	Fixed Pole Specific length 2" diameter. Specify length and add \$4.50 per foot up to 10'	\$26.00
PL-1.5 - SPEC	Fixed Pole Specific length 1.5" diameter specify length and add \$4.50 per foot up to 10'	\$26.00
PLMT-EX	Pole Mount Extender Female to Female threaded collar to allow two 2" poles to be extended.	\$26.00

Model #	Flat Panel Display Ceiling Mounts- Upper Components	List
PLMT-T	Pole Mount Top Panel Mounting Panel with threaded collar for 2" pole. Attaches to structural ceiling. Requires pole and PCM mounting adapter to complete system.	\$71.00
PS-Kit	Pole Stabilizing Kit Attaches to 2" pole to stabilize from three points of structural ceiling. Uses either wire rope, 3/8" threaded rod or 1" conduit supplied by installer.	\$178.00
PSV-Kit	Pole Stabilizing / Anti-Vibration Kit. Attaches to 2" pole to stabilize from three points of structural ceiling. Includes Anti-Vibration mounting points. Uses either wire rope, 3/8" threaded rod or 1" conduit supplied by installer.	\$320.00
CTP-2x2	Ceiling Tile Panel for stationary mounting of projectors and PDP's. Provides versatile mounting positions in 2 ft. X 2 ft. drop tile. Requires pole and mount to complete system.	\$195.00
PLMT-T	Pole Mount Top Panel Mounting Panel with threaded collar for 2" pole. Attaches to structural ceiling. Requires pole and PCM mounting adapter to complete system.	\$71.00
PLMT-VIT	Pole Mount Top Panel w/ Vibration Isolation Attaches to structural ceiling for isolation of 2" pole. Must be purchased with complete PLMT system.	\$135.00
PLMT-AA	Pole Mount Angle Adapter. Angled mounting panel with threaded collar for 2" pole. For cathedral style ceilings; 0° - 90°. Requires pole and PCM mounting adapter to complete system. 150# weight limit.	\$115.00
Model #	Flat Panel Rotating Ceiling Mount	List
RCM	Rotating Ceiling Mount Manual rotation of display. Cannot be used on lift. Requires pole, PCM and PLMT-T / AA / U / C / CTP2X2 to complete system.	\$178.00
MRCM	Motorized Rotating Ceiling Mount Rotates display product to two programmable show positions. Cannot be used on lift. 250 lb. capacity. Contact closure remote port. Requires 2" diameter pole and projector mount to complete system. 110V. Optional wall mounted remotes available.	\$1,850.00
MRCM 220V	Motorized Rotating Ceiling Mount Rotates display product to two programmable show positions. Cannot be used on lift. 250 lb. capacity. Contact closure remote port. Requires 2" diameter pole and projector mount to complete system. 220V. Optional wall mounted remotes available.	\$1,850.00
iMRCM	Continuous Motorized Rotating Ceiling Mount Rotates flat panel displays with uninterrupted signal connection. Cannot be used on lift. Contact closure remote port. Requires DDI 2" and flat panel mounts to complete system. 110V, 250 lb capacity. Optional multiple display mount; contact our sales department.	\$2,853.00

iMRCM 220V	Continuous Motorized Rotating Ceiling Mount Rotates flat panel displays with uninterrupted signal connection. Cannot be used on lift. Contact closure remote port. Requires DDI 2" and flat panel mounts to complete system. 220V, 250 lb capacity. Optional multiple display mount; contact our sales department.	\$2,853.00
WPR-M01-W	Wall Plate Remote panel for iMRCM/MRCM. Single gang white.	\$75.00
WPR-M01-B	Wall Plate Remote panel for iMRCM/MRCM. Single gang black.	\$75.00
WPR-M01-S	Wall Plate Remote panel for iMRCM/MRCM. Single gang brushed steel .	\$75.00
REM-M19- RM	Rack mount Panel Remote wired control panel for iMRCM/MRCM 1.75" x 19" EIA. Black	\$75.00
REM-M02-W	Locking Wall Plate Remote wired control panel for iMRCM/MRCM with security key lock. 2 gang, white	\$115.00
REM-M02-B	Locking Wall Plate Remote wired control panel for iMRCM/MRCM with security key lock. 2 gang, black	\$115.00
REM-M02-S	Locking Wall Plate Remote wired control panel for MRCM with security key lock. 2 gang, brushed steel	\$115.00

Model #	Protective Bezel Covers & Indoor Enclosures	List
PBz-1727	Protective Bezel Cover - 17"-27" : for most commercial LCD monitors 17"-27". 16 gauge steel frame with 6 mm abrasion-resistant, clear polycarbonate window. Specify make & model of display and Portrait or Landscape mode. Powdercoat black, white or silver finish. Other colors optional. <i>Flat panel wall mount sold separately.</i>	\$607.00
PBz-2839	Protective Bezel Cover - 28"-39" : for most commercial flat panel displays 28"-39". 16 gauge steel frame with 6 mm abrasion-resistant, clear polycarbonate window. Specify make & model of display and Portrait or Landscape mode. Powdercoat black, white or silver finish. Other colors optional. <i>Flat panel wall mount sold separately.</i>	\$709.00
PBz-4046	Protective Bezel Cover - 40"-46" : for most commercial flat panel displays 40"-46". 16 gauge steel frame with 6 mm abrasion-resistant, clear polycarbonate window. Specify make & model of display and Portrait or Landscape mode. Powdercoat black, white or silver finish. Other colors optional. <i>Flat panel wall mount sold separately.</i>	\$850.00
PBz-4754	Protective Bezel Cover - 47"-54" : for most commercial flat panel displays 47"-54". 16 gauge steel frame with 6 mm abrasion-resistant, clear polycarbonate window. Specify make & model of display and Portrait or Landscape mode. Powdercoat black, white or silver finish. Other colors optional. <i>Flat panel wall mount sold separately.</i>	\$1,137.00
PBz-5564	Protective Bezel Cover - 55"-64" : for most commercial flat panel displays 55"-64". 16 gauge steel frame with 6 mm abrasion-resistant, clear polycarbonate window. Specify make & model of display and Portrait or Landscape mode. Powdercoat black, white or silver finish. Other colors optional. <i>Flat panel wall mount sold separately.</i>	\$1,280.00
PBz-6570	Protective Bezel Cover - 65"-70" : for most commercial flat panel displays 65"-70". Lightweight aluminum frame with 1/2" abrasion-resistant, clear polycarbonate window. Specify make & model of display and Portrait or Landscape mode. Powdercoat black, white or silver finish. Other colors optional. <i>Flat panel wall mount sold separately.</i>	\$1,567.00
TSB-1027	27-31" Touch Screen Bezel Cover for most commercial 27-31" flat panel displays. Lightweight aluminum frame with 1/4" abrasion-resistant, clear polycarbonate window. Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 60 Million actuations life, 92%-100% transmission accuracy, no drift. Specify make & model of display and Portrait or Landscape mode. Powdercoat black, white or silver finish. Other colors optional.	\$2,521.00

TSB-1032	32-37" Touch Screen Bezel Cover for most commercial 32-37" flat panel displays. Lightweight aluminum frame with 1/4" abrasion-resistant, clear polycarbonate window. Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 60 Million actuations life, 92%-100% transmission accuracy, no drift. Specify make & model of display and Portrait or Landscape mode. Powdercoat black, white or silver finish. Other colors optional.	\$2,807.00
TSB-1042	38-42" Touch Screen Bezel Cover for most commercial 38-42" flat panel displays. Lightweight aluminum frame with 1/2" abrasion-resistant, clear polycarbonate window. Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 60 Million actuations life, 92%-100% transmission accuracy, no drift. Specify make & model of display and Portrait or Landscape mode. Powdercoat black, white or silver finish. Other colors optional.	\$3,428.00
TSB-1050	43- 50" Touch Screen Bezel Cover for most commercial 43-50" flat panel displays. Lightweight aluminum frame with 1/2" abrasion-resistant, clear polycarbonate window. Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 60 Million actuations life, 92%-100% transmission accuracy, no drift. Specify make & model of display and Portrait or Landscape mode. Powdercoat black, white or silver finish. Other colors optional.	\$3,928.00
PE-VENT-30P/L	Up to 37" Indoor Panel Enclosure: All-metal, NEMA12 enclosure with 1/2" abrasion-resistant, clear polycarbonate window. Perforated top & bottom panels for ventilation. Removable front access door with security hardware. Includes flat panel mount adapter. Specify make & model display and Portrait or Landscape mode. Black, Silver or White powdercoat finish.	\$2,285.00
PE-VENT-40P/L	38"-42" Indoor Panel Enclosure: All-metal, NEMA12 enclosure with 1/2" abrasion-resistant, clear polycarbonate window. Perforated top & bottom panels for ventilation. Removable front access door with security hardware. Includes flat panel mount adapter. Specify make & model display and Portrait or Landscape mode. Black, Silver or White powdercoat finish.	\$2,700.00
PE-VENT-50P/L	43"-56" Indoor Panel Enclosure: All-metal, NEMA12 enclosure with 1/2" abrasion-resistant, clear polycarbonate window. Perforated top & bottom panels for ventilation. Removable front access door with security hardware. Includes flat panel mount adapter. Specify make & model display and Portrait or Landscape mode. Black, Silver or White powdercoat finish.	\$3,642.00

PE-VENT-60P/L	57"-70" Indoor Panel Enclosure: All-metal, NEMA12 enclosure with 1/2" abrasion-resistant, clear polycarbonate window. Perforated top & bottom panels for ventilation. Removable front access door with security hardware. Includes flat panel mount adapter. Specify make & model display and Portrait or Landscape mode. Black, Silver or White powdercoat finish.	\$4,071.00
Model #	Outdoor Flat Panel Enclosures	List
PE-40P/L	38"-42" Indoor/Outdoor Panel Enclosure: All-metal, NEMA12 enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Louvered / filtered intake and exhaust ports for thermostatically controlled circulation fans. Programmable, digital thermostat with RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V. Designed for total power consumption of enclosed products <350W and ambient temperature range 35°-90° F. Powdercoat black, white or silver finish. Other colors optional. Specify flat panel display make & model and Portrait or Landscape mode.	\$4,750.00
PE-50P/L	43"-56" Indoor/Outdoor Panel Enclosure: All-metal, NEMA12 enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Louvered / filtered intake and exhaust ports for thermostatically controlled circulation fans. Programmable, digital thermostat with RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V. Designed for total power consumption of enclosed products <350W and ambient temperature range 35°-90° F. Powdercoat black, white or silver finish. Other colors optional. Specify flat panel display make & model and Portrait or Landscape mode.	\$5,655.00
PE-60P/L	57"-70" Indoor/Outdoor Panel Enclosure: All-metal, NEMA12 enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Louvered / filtered intake and exhaust ports for thermostatically controlled circulation fans. Programmable, digital thermostat with RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V. Designed for total power consumption of enclosed products <350W and ambient temperature range 35°-90° F. Powdercoat black, white or silver finish. Other colors optional. Specify flat panel display make & mode and Portrait or Landscape mode.	\$6,680.00

PE-AC-40P/L	38-42" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 2200BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V. Designed for total power consumption of enclosed products <750W and ambient temperature range 35°-110° F. Specify flat panel display make & model and Portrait or Landscape mode.	\$7,565.00
PE-AC-50P/L	43-56" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 2200BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V. Designed for total power consumption of enclosed products <750W and ambient temperature range 35°-110° F. Specify flat panel display make & model and Portrait or Landscape mode.	\$8,470.00
PE-AC-60P/L	57-70" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 3500BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V. Designed for total power consumption of enclosed products <1100W and ambient temperature range 35°-110° F. Specify flat panel display make & model and Portrait or Landscape mode.	\$9,985.00
Model #	Outdoor Flat Panel Enclosure Options	List
OPT-ACCR	Corrosion resistant package for NEMA3R4 - option for PE-AC. Upgrades Air-conditioner to all-stainless steel construction. Recommended for ocean air environments	\$2,000.00
OPT-Heat	Heating Sub System Provides heating to any PE and PE-AC Panel Enclosure. Designed to elevate interior temperature up to panel's proper operating range. Extends lower temp range to sub-zero.	\$715.00
PE-WM-VT	Tilting Wall Mount for PE / PE-AC. Provides adjustable tilt to a wall mounted Panel Enclosure. Capacity 250 Lbs.Variable downward tilt of 5, 10 or 15 degrees. Powdercoat finish to match PE.	\$690.00

PE-Ped-40-P/L	Pedestal for PE-40 / PE-AC-40 with base - same dimensional as enclosure accessories to your specification. Heavy gauge steel construction, access door, floor base. Specify required height. <i>Complies with ADA Requirements.</i>	\$372.00
PE-Ped-50-P/L	Pedestal for PE-50 / PE-AC-50 with base - same dimensional as enclosure accessories to your specification. Heavy gauge steel construction, access door, floor base. Specify required height. <i>Complies with ADA Requirements.</i>	\$435.00
PE-Ped-60-P/L	Pedestal for PE-60 / PE-AC-60 with base - same dimensional as enclosure accessories to your specification. Heavy gauge steel construction, access door, floor base. Specify required height. <i>Complies with ADA Requirements.</i>	\$680.00
OPT-OTS-32	Touchscreen for 32" Panel Enclosure - Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 7 year or 60 Million actuations life, 92%-100% transmission accuracy, no drift, vandal proof.	\$2,180.00
OPT-OTS-42	Touchscreen for 40-42" Panel Enclosure - Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 7 year or 60 Million actuations life, 92%-100% transmission accuracy, no drift, vandal proof.	\$2,589.00
OPT-OTS-50	Touchscreen for 50" Panel Enclosure - Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 7 year or 60 Million actuations life, 92%-100% transmission accuracy, no drift, vandal proof.	\$3,214.00

Model #	Flat Panel and Plasma Lifts	List
TFT-55 110V	Monitor Lift to raise smaller flat panel displays out of conference tables, podiums or desks or lower flat panel displays from cabinetry. Travels 14" maximum (approximate 21" monitor max - varies by make/model) Includes VESA 75 / 100 mount. 120lb. weight capacity. Specify make/model monitor. 110V.	\$990.00
TFT-55 220V	Monitor Lift to raise smaller flat panel displays out of conference tables, podiums or desks or lower flat panel displays from cabinetry. Travels 14" maximum (approximate 21" monitor max - varies by make/model) Includes VESA 75 / 100 mount. 120lb. weight capacity. Specify make/model monitor. 220V.	\$990.00
TFT-75 110V	Monitor Lift to raise smaller flat panel displays out of conference tables, podiums or desks or lower flat panel displays from cabinetry. Travels 20" maximum (approximate 27" monitor max - varies by make/model) Includes VESA 75 / 100 mount. 120lb. weight capacity. Specify make/model monitor. 110V.	\$1,190.00
TFT-75 220V	Monitor Lift to raise smaller flat panel displays out of conference tables, podiums or desks or lower flat panel displays from cabinetry. Travels 20" maximum (approximate 27" monitor max - varies by make/model) Includes VESA 75 / 100 mount. 120lb. weight capacity. Specify make/model monitor. 220V.	\$1,190.00
Top bracket	Top bracket for TFT-55/75. To allow opening and closing of hinged table top. For use with table top material up to 1" (2.54mm) thick .	\$104.30
PL-2200i	PlasmaLift for 40" to 50" display panels designed to raise 41". Basic configuration for installation in custom furniture, includes wired handheld remote. 110V. Includes finger safety guard. <i>Includes universal mount- fits most 40"-50" displays.</i>	\$3,150.00
OPT-20	Enclosure Frame and adjustable top panel mount for PL-1700i, PL-2200i or PL-2260 . Specify dimensions of any optional products to be raised such as speakers, cameras, etc..	\$835.00
PL-2200i 220V	PlasmaLift for 40" to 50" display panels designed to raise 41". Basic configuration for installation in custom furniture, includes wired handheld remote. 220V. Includes finger safety guard. <i>Includes universal mount- fits most 40"-50" displays.</i>	\$3,150.00
PL-2260i	PlasmaLift for 61"+ display panels designed to raise 41". Basic configuration for installation in custom furniture, includes wired handheld remote. Includes finger safety guard. 110V. PM-### required.	\$3,430.00

PM-###	Panel Mount. Flat Panel Mounting Adapter for flat panel display. Specify Make / Model # of display panel. See flat panel adapter list for exact part #.	\$170.00
PL-2260i 220V	PlasmaLift for 61"+ display panels designed to raise 41". Basic configuration for installation in custom furniture, includes wired handheld remote. Includes finger safety guard. 220V. PM-### required.	\$3,430.00
PL-3042	Ceiling PlasmaLift for 40/42" display panels designed to lower 40" with panel tilt from ceiling space. Includes plenum enclosure, hinged ceiling closure frame, wired remote. 110V. <i>Includes universal mount- fits most 40"-50" displays.</i>	\$4,000.00
PL-3042 220V	Ceiling PlasmaLift for 40/42" display panels designed to lower 40" with panel tilt from ceiling space. Includes plenum enclosure, hinged ceiling closure frame, wired remote. 220V. <i>Includes universal mount- fits most 40"-50" displays.</i>	\$4,000.00
PL-3050	Ceiling PlasmaLift for 50" display panels designed to lower 40" with panel tilt from ceiling space. Includes plenum enclosure, hinged ceiling closure frame, wired remote. 110V. <i>Includes universal mount- fits most 40"-50" displays.</i>	\$4,000.00
PL-3050 220V	Ceiling PlasmaLift for 50" display panels designed to lower 40" with panel tilt from ceiling space. Includes plenum enclosure, hinged ceiling closure frame, wired remote. 220V. <i>Includes universal mount- fits most 40"-50" displays.</i>	\$4,000.00
PL-3060	Ceiling PlasmaLift for 61"+ display panels, designed to lower display 49" from ceiling. Includes plenum enclosure, hinged ceiling closure frame, wired remote. 110V. PM-### required.	\$5,500.00
PL-3060 220V	Ceiling PlasmaLift for 61"+ display panels, designed to lower 49" from ceiling. Includes plenum enclosure, hinged ceiling closure frame, wired remote. 220V. PM-### required.	\$5,500.00
PL-3242	Ceiling PlasmaLift for 40/42" display panels designed to lower from ceiling. Maximum screen size: 41.5" w X 25" h. Slim profile design of 7.5" depth. Provides up to 70" travel distance and programmable show position. Dry contact closure. 110V. PM-### required.	\$4,000.00
PL-3242 220V	Ceiling PlasmaLift for 40/42" display panels designed to lower from ceiling. Maximum screen size: 41.5" w X 25" h. Slim profile design of 7.5" depth. Provides up to 70" travel distance and programmable show position. Dry contact closure. 220V. Includes PM-### required.	\$4,000.00
PL-3250	Ceiling PlasmaLift for 50" display panels to lower from ceiling. Maximum screen size: 49" w X 29" h. Slim profile design of 7.5" depth. Provides up to 70" travel distance and programmable show position. Dry contact closure. 110V. PM-### required.	\$4,000.00

PL-3250 220V	Ceiling PlasmaLift for 50" display panels to lower from ceiling. Maximum screen size: 49" w X 29" h. Slim profile design of 7.5" depth. Provides up to 70" travel distance and programmable show position. Dry contact closure. 220V. PM-### required.	\$4,000.00
Model #	Flat Panel Lift Options	List
OPT-11-C	Cable Pre Wire Prewire of any PL series plasma lift with control, signal and power cabling.	\$400.00
OPT-20	Enclosure Frame and adjustable top panel mount for PL-2200i or PL-2260 . Specify dimensions of any optional products to be raised such as speakers, cameras, etc..	\$835.00
PCS-02	Power Current Sensor. Ultra sensitive current sensing of projectors and display panels. 110V. Provides contact closure out.	\$111.00
REM-IR	Wireless Infrared Remote control. May be used with any motorized DDI product.	\$285.00
REM-RF	Wireless Radio Frequency Remote control May be used with any motorized DDI product.	\$357.00
WPR-P01-W	Wall Plate Remote panel for all PlasmaLifts. Single gang white. 3 button - Up, Down, Stop & programming.	\$75.00
WPR-P01-B	Wall Plate Remote panel for all PlasmaLifts. Single gang black. 3 button - Up, Down, Stop & programming.	\$75.00
WPR-P01-S	Wall Plate Remote panel for all PlasmaLifts. Single gang brushed steel. 3 button - Up, Down, Stop & programming.	\$75.00
REM-P19- RM	Rack mount Panel Remote wired control panel for all PlasmaLifts. 1.75" x 19" EIA. Black. 3 button - Up, Down, Stop & programming.	\$75.00
REM-P02-W	Locking Wall Plate Remote wired control panel with security key lock. 4" x 4". Double gang, white. 3 button - Up, Down, Stop & programming.	\$115.00
REM-P02-B	Locking Wall Plate Remote wired control panel with security key lock. 4" x 4". Double gang, black. 3 button - Up, Down, Stop & programming.	\$115.00
REM-P02-S	Locking Wall Plate Remote wired control panel with security key lock. 4" x 4". Double gang, brushed steel. 3 button - Up, Down, Stop & programming.	\$115.00
Model #	Specialty Flat Panel Display Mounts	List
PWM-WR- ###	Wire Rope Flat Panel Mount - System includes flat panel mount and 3/32" wire rope hardware. User must provide structural attachment and 3/32" wire rope. Specify display make and model; 30 - 50" display panels. 90 # weight capacity.	\$530.00

PLMT-WA-7	Pole Mount Wall Arm Arm mounts to wall provided with 2" threaded collar. Mounts displays 7" from wall. Pole and SPD required to complete system.	\$98.00
PLMT-WA-12	Pole Mount Wall Arm Arm mounts to wall provided with 2" threaded collar. Mounts displays 12" from wall. Pole and SPD required to complete system.	\$115.00
RBW-001b	RackBack Wall Mount. 1 RU EIA 19" chassis to rack mount equipment behind a flat panel display, includes 2 security covers.	\$245.00
RBW-002b	RackBack Wall Mount 2 RU EIA 19" chassis to rack mount equipment behind a flat panel display, includes 2 security covers.	\$260.00
RB-001b	RackBack Mount 1 RU EIA 19" enclosed chassis to rack mount equipment behind a flat panel display, includes 2 security covers.	\$245.00
RB-002b	RackBack Mount 2 RU EIA 19" enclosed chassis to rack mount equipment behind a flat panel display, includes 2 security covers.	\$260.00
MRWM	Motorized Rotating Wall Mount for Flat Panel Display. Rotates from Landscape to Portrait orientation. System includes wall mounting rails and motorized rotation. Operates via contact closure. Includes positional feedback. 90 pound weight capacity. Requires MPM-###; specify display panel make & model.	\$2,115.00
OPT-9	RS-232 Serial control interface - allows for variable speed when using a third party control system (Crestron/AMX).	\$300.00
iMRWM	intelligent Motorized Rotating Wall Mount for Small sized Flat Panel Displays. Continuous Rotation through Landscape, Portrait orientation and beyond. System includes wall mounting rails and continuous rotation. Operates via contact closure or RS-232 serial control of direction, position, and speed. 90 pound weight capacity, specify display make and model.	\$3,270.00
OPT-DMX	DMX Serial control interface - Replaces RS-232	\$300.00
Model #	Flat Panel Display Wall Mounts	List
PWM-UNIV	Flat Panel Universal Wall Mount fits most 30" - 61" flat panel displays. Wall plate and two locking mount rails with 0°-15° tilt adjustment. 200 lbs weight capacity. Specify color: (B)Black or (S)Silver.	\$280.00
PWM-###	Flat Panel Wall Mount System includes mounting rails and flat panel mount. Specify display make and model; 30 - 63" display panels.	\$235.00
PWM-T-###	Flat Panel Wall Mount with Tilt System includes mounting rails, tilt assembly and flat panel mount. Specify display make and model; 30 - 63" display panels.	\$345.00

Model #	Articulating Flat Panel Display Wall Mounts	List
PWM-AA-6-###	Flat Panel Articulating Wall Mount with 6" extension. Low Profile (2.25" depth) for recessed display mounting, 125 Lb capacity. Includes mounting plate, articulating assembly and display panel mount. Specify display make and model; 30 - 50" display panels.	\$345.00
PWM-AA-12-###	Flat Panel Articulating Wall Mount with 12" extension Compact design (3.6" depth), 125 Lb capacity*. Includes mounting plate, articulating assembly and display panel mount. Specify display make and model; 30 - 63" display panels. *Will support higher weights but downward deflection will occur when extended.	\$650.00
PWM-AA-36-###	Flat Panel Articulating Wall Mount with 36" extension Compact design 2.0" depth, 140 Lb capacity, 30 - 63" display panels. Includes mounting plate, articulating assembly and display panel mount. Specify display make and model.	\$500.00
Model #	VESA 75 - 100mm Display Panel Wall Mounts	List
VWM-01	Display Panel Wall Mount for VESA 75mm and 100mm standard. Provides Up - Down tilt only. Specify display make and model; 12 - 25" display panels.	\$70.00
VWM-02	Display Panel Wall Mount for VESA 75mm and 100mm standard. Provides Up - Down tilt and Right - Left pivot adjustments. Specify display make and model; 12 - 25" display panels.	\$80.00
VWM-03	Display Panel Wall Mount for VESA 75mm and 100mm standard. Provides Up - Down tilt and Right - Left pivot with single 6" extension arm adjustments. Specify display make and model; 12 - 25" display panels.	\$110.00
VWM-04	Display Panel Wall Mount for VESA 75mm and 100mm standard. Provides Up - Down tilt and Right - Left pivot with Dual 9" extension arm adjustments. Specify display make and model; 12 - 25" display panels.	\$135.00
Model #	Vogels Ceiling Mounts for Flat Displays	List
FAU 3125	Display mount adapter for VESA 75-100-200	\$124.00
FAU 3150	Display mount adapter for 30-65" Universal	\$221.00
PFA 9001	Lower mount section w/Turn & tilt for single display (SPD)	\$238.00
PFA 9002	Lower mount section w/Turn & tilt for dual displays (DPD)	\$294.00
PFA 9003	Tube 1.5m / 60"	\$144.00
PFA 9004	Tube 3m / 118"	\$283.00
PFA 9010	Ceiling plate	\$63.00
PFA 9015	Tube 31.5"	\$94.00

Model #	Vogels Floor Stands for Flat Displays	List
FAU 3125	Display mount adapter for VESA 75-100-200	\$124.00
FAU 3150	Display mount adapter for 30-65" Universal	\$221.00
PFA 9033	Tray for PFF 2410, PFT 2300, 2510	\$270.00
PFA 9034	Locking cabinet for PFF 2410, PFT 2300, 2510	\$450.00
PFA 9035	Video conference camera holder	\$141.00
PFF 2410	Display floorstand	\$1,730.00
PFT 2505	Display trolley, low	\$1,405.00
PFT 2510	"Brand Your Stand" trolley for 32-55", 121 lb. cap. Height 45-69" adjustable	\$1,842.00
PFF 1500	Display floorstand	\$1,750.00
PFF 1550	Stainless steel floostand, 60" tall	\$1,539.00
PFF 1570	Stainless steel floostand, 67" tall	\$1,599.00
PFT 2010	Display trolley, heavy duty	\$3,387.00
PFT 2100	Display trolley	\$1,750.00
EFA 6825	Audio/DVD Support	\$87.00
EFA 6840	Cable column, 36"	\$123.00
EFA 6895	Universal stud adapter	\$133.00
Model #	Vogels Universal Wall Mounts	List
PFW 5005	Wall support full lock, for 37-50" 110 lb capacity, superflat	\$154.00
PFW 5010	Wall support tilting full lock, for 37-50" 110 lb capacity, superflat	\$178.00
PFW 5505	Wall support full lock, for 50-70" 165 lb capacity, superflat	\$171.00
PFW 5510	Wall support tilting full lock, for 50-70" 165 lb capacity, superflat	\$198.00
PFW 5000	Wall support semi-lock, for 37-50" 110 lb capacity, superflat	\$128.00
PFW 5500	Wall support semi-lock, for 50-70" 165 lb capacity, superflat	\$147.00
Model #	Vogels Wall Mounts with Articulating Arms	List
EFW 6245	LCD wall support with tilt,turn,reach,23-32" 55 lb cap. VESA 75-100-200	\$349.00
EFW 6345	LCD wall support with tilt,turn,reach,31-42" 94 lb cap. Universal mount	\$523.00
EFW 6445	LCD wall support with tilt,turn,reach,42-70" 121 lb cap. Universal mount	\$696.00
VFW 232	LCD wall support, 1 pivot turn & tilt, 23-32" 70 lb capacity, VESA 75-100-200	\$129.00
VFW 332	LCD wall support, 2 pivot turn & tilt, 23-32" 70 lb capacity, VESA 75-100-200	\$203.00
VFW 432	LCD wall support, 3 pivot turn & tilt, 23-32" 70 lb capacity, VESA 75-100-200	\$277.00
EFWE 6455 RC	GLIDER wall support, 42-60" 154 lb capacity. Universal mount	\$1,320.00

Model #	Media Server	List
AMS-SC-C2D	AdEdge Media Server - Core2Duo Model. Compact, rugged design for 24/7 digital signage applications. 1.66GHz Core2Duo processor, supports HD resolution (1920x1080i), premium audio, video, storage and wireless specs.	\$1,990.00
Model #	Microphone Lifts & Flips	List
ML-8sBK	Microphone Lift System - lowers microphone down 8' with a programmable stop point. 110V, 10 oz weight capacity , dry contact closure, XLR-F audio connection, hand-held hardwired remote control. BLACK cable.,Mic not included - Integration of your microphone at NO CHARGE. Specify make & model number of microphone.	\$1,780.00
ML-8sBK 220V	Microphone Lift System - lowers microphone down 8' with a programmable stop point. 220V, 10 oz weight capacity , dry contact closure, XLR-F audio connection, hand-held hardwired remote control. BLACK cable.,Mic not included - Integration of your microphone at NO CHARGE. Specify make & model number of microphone.	\$1,780.00
ML-8sBG	Microphone Lift System - lowers microphone down 8' with a programmable stop point. 110V, 10 oz weight capacity , dry contact closure, XLR-F audio connection, hand-held hardwired remote control. BEIGE cable, mic not included - Integration of your microphone at NO CHARGE. Specify make & model number of microphone.	\$1,780.00
ML-8sBG 220V	Microphone Lift System - lowers microphone down 8' with a programmable stop point. 220V, 10 oz weight capacity , dry contact closure, XLR-F audio connection, hand-held hardwired remote control. BEIGE cable, mic not included - Integration of your microphone at NO CHARGE. Specify make & model number of microphone.	\$1,780.00
ML-25sBK	Microphone Lift System - lowers microphone down 25' with a programmable stop point. 110V, 4 oz weight capacity , dry contact closure, XLR-F audio connection, hand-held hardwired remote control. BLACK cable, mic not included - Integration of your microphone at NO CHARGE. Specify make & model number of microphone.	\$2,125.00
ML-25sBK 220V	Microphone Lift System - lowers microphone down 25' with a programmable stop point. 220V, 4 oz weight capacity , dry contact closure, XLR-F audio connection, hand-held hardwired remote control. BLACK cable, mic not included - Integration of your microphone at NO CHARGE. Specify make & model number of microphone.	\$2,125.00

ML-25sBG	Microphone Lift System - lowers microphone down 25' with a programmable stop point. 110V, 4 oz weight capacity , dry contact closure, XLR-F audio connection, hand-held hardwired remote control. BEIGE cable, mic not included - Integration of your microphone at NO CHARGE. Specify make & model number of microphone.	\$2,125.00
ML-25sBG	Microphone Lift System - lowers microphone down 25' with a programmable stop point. 220V, 4 oz weight capacity , dry contact closure, XLR-F audio connection, hand-held hardwired remote control. BEIGE cable, mic not included - Integration of your microphone at NO CHARGE. Specify make & model number of microphone.	\$2,125.00
ML-EX	Collar Extender Kit for microphone retraction column on ML-8s 7 ML-25s. Adds 1.38" vertical to the column per EX kit.	\$36.00
MFD-50	Microphone Flipation Device. Manual Flipation of boundry microphone from table surface. Allows mic to disappear below table when not in use. Mic not included. Installation requires skilled mill work.	\$575.00
MFD-100	Microphone Flipation Device. Motorized Flipation of boundry microphone from table surface. Allows mic to disappear below table when not in use. 110V, dry contact closure, hand-held hardwired remote control included. Mic not included. Installation requires skilled mill work.	\$1,250.00
MFD-100 220V	Microphone Flipation Device. Motorized Flipation of boundry microphone from table surface. Allows mic to disappear below table when not in use. 220V, dry contact closure, hand-held hardwired remote control included. Mic not included. Installation requires skilled mill work.	\$1,250.00

Camera Pan / Tilt System		
Model #	Pan / Tilt Controllers	List
DDI PT-C55	Desktop Joystick Pan Tilt Control Panel. Control up to 8 Pan Tilt Heads. Recall up to 20 Presets per head. Proportional Speed control. Proportional toggle zoom and twist focus control. *Provides basic CCU functionality for select cameras with CCB option.	\$1,950.00
DDI PT-C	Desktop Dual Joystick Control Panel (pan / tilt & zoom / focus). Control up to 32 Pan Tilt Heads. Recall up to 64 Presets per head. Proportional Speed control with 3 speed ranges. Alpha-numeric display. RS-485 control protocol.	\$1,600.00
DDI PT-CC	Desktop Camera Control Unit for control of up to 32 cameras. Requires DDIC-101 and 1 ea. DDI-CCB per camera head. *Level of CCU functionality depends upon make & model camera.	\$1,120.00
DDI PT-TSC2	Color Touch Screen Controller w/ proportional digital joystick for control of pan-tilt and focus. Rocker for zoom control. Controls up to 125 Pan Tilt Heads/cameras. CCU functions w/ opt. DDI-CCB. Proportional speed & RS-485 control.	\$6,300.00
Model #	Pan / Tilt Heads & Head Accessories	List
DDI PT-50 BK	Mini Interior Pan Tilt Head. 6 Lb. weight capacity. Variable speed/Vector solving motion. Internal nonvolatile preset memory. Integrated 12VDC out f/ cam. RS-485 / 232 control protocol. Stylish black finish. Requires Telecon lens. Composite vid out.	\$2,540.00
DDI PT-50TA	Tally Light option for any PT-50 HEAD. Requires PT-CSI.	\$310.00
DDI PT-50COMP BK	Mini Interior Pan Tilt Head. 6 Lb. weight capacity. Variable speed/Vector solving motion. Internal nonvolatile preset memory. Integrated 12VDC out f/ cam. RS-485 / 232 control protocol. Stylish black finish. Requires Telecon lens. Component vid out.	\$2,625.00
DDI PT-50SDI BK	Mini Interior Pan Tilt Head. 6 Lb. weight capacity. Variable speed/Vector solving motion. Internal nonvolatile preset memory. Integrated 12VDC out f/ cam. RS-485 / 232 control protocol. Stylish black finish. Requires Telecon lens. SDI video out.	\$3,685.00
DDI PT-CCB-50	Camera Control Module. Installs within DDI-50 to provide CCU communication between camera and DDI-CCU. *Level of CCU functionality depends upon make & model camera.	\$215.00

DDI-PT101 BK	Interior Pan Tilt Head with Dual BNC connectors. 14 Lb. weight capacity. Variable speed/Vector solving motion. Int. nonvolatile preset memory. 12VDC out f/ cam. RS-485 / 232 control. Black finish. *Requires Telecon lens. Composite vid out.	\$4,255.00
DDI PT-101COMP	Interior Pan Tilt Head with Dual BNC connectors. 14 Lb. weight capacity. Variable speed/Vector solving motion. Int. nonvolatile preset memory. 12VDC out f/ cam. RS-485 / 232 control. Black finish. *Requires Telecon lens. Component vid out.	\$4,340.00
DDI PT-101TA	Tally Light option for any PT-101 HEAD. Requires PT-CSI.	\$180.00
DDI PT-101SDI	Interior Pan Tilt Head with Dual BNC connectors. 14 Lb. weight capacity. Variable speed/Vector solving motion. Int. nonvolatile preset memory. 12VDC out f/ cam. RS-485 / 232 control. Black finish. *Requires Telecon lens. SDI vid out.	\$5,400.00
DDI PT-CCB-101	Camera Control Module. Installs within DDI-101 to provide CCU communication between camera and DDI-CCU. *Level of CCU functionality depends upon make & model camera.	\$215.00
DDI-PT250	Heavy duty Indoor Pan Tilt Head. 40 Lb. weight capacity. Variable speed/Vector solving motion. Internal nonvolatile preset memory. Integrated 12VDC out f/ cam. RS-485 control protocol. Stylish black finish. *Requires Telecon lens. Composite vid out.	\$4,700.00
DDI PT-250TA	Tally Light option for any PT-250 HEAD. Requires PT-CSI.	\$310.00
DDI-PTE350	Heavy duty Outdoor Pan Tilt Head. Requires Environmental Enclosure (see Accessories) for outdoor applications. 50 Lb. weight capacity. Variable speed/Vector solving motion. Internal nonvolatile preset memory. Integrated 12VDC out f/ cam. RS-485 control protocol. *Requires Telecon lens. Composite vid out.	\$5,410.00
DDI PT-CCB-101	Camera Control Board. Installs within DDI-101, PT-250 OR PT-350 to provide CCU communication between camera and DDI-CCU. *Level of CCU functionality depends upon make & model camera.	\$215.00
Model #	Pan / Tilt Mounts	List
DDI PT-CM-50	Indoor Ceiling Mount adapter for DDI-50 only	\$130.00
DDI PT-CM-101	Indoor Ceiling Mount adapter for DDI-101 only	\$130.00
DDI-WM-12	Wall Mount for DDI-50. 12" long.	\$122.00
DDI-WM-18	Wall Mount for DDI-101, DDI-250HD. 18" long w/diagonal brace.	\$122.00
DDI-PM-24	Parapet Mount for DDI-350 for outdoor applications.	\$385.00

DDI PT-PED2	Pedevator version 2. Heavy duty motorized elevator column. for indoor studio use	\$4,900.00
Model #	Pan / Tilt Power Supplies	List
DDI PT-AAM	Auto Answer Modem (Each includes 1 PT-RSA)	\$250.00
DDI PT-BB	Control Box	\$846.00
PT-CSI	Contact To Serial Interface	\$710.00
PS-24-2.5	Power Supply. 24VDC / 3.0A Use with single DDI-50 or DDI-101 w/ camera.	\$230.00
PS-24-6.5	Power Supply. 24VDC / 6.5A. Use with single DDI-101 / DDI-250hd w/ camera.	\$340.00
PS-24-12	Power Supply. 24VDC / 12.0A; 4 outputs of 3A / each. Use with 4ea DDI-50 or DDI-101's w/cameras	\$540.00
PS-24-6.5E	Power Supply w/ NEMA 4X Outdoor Enclosure. 24VDC / 6.5A. Use with DDI-350 w/ camera.	\$520.00
PS-24-20	Power Supply. 24VDC / 20A. Use with large Multi-Head systems.	\$855.00
Model #	Control & Environmental Accessories	List
DDI-PT-SB	Shot box for recording and replaying live action camera moves	\$925.00
DDI PT-EE-S	Small Environmental Camera Enclosure for PTE-300, 350 (FORHV-D30 SYSTEMS)	\$635.00
DDI PT-EE-L	Large Environmental Camera Enclosure for PTE-300, 350 (FORHV-D15, D25 SYSTEMS WITH 16X or -300, 350.	\$910.00
DDI-EE-HTR	Heater option for DDI-Environmental Enclosures.	\$270.00
DDI PT-DEF	Window Defroster / Defogger Kit option for DDI-Environmental Enclosures.	\$135.00
DDI-1x6	Control + DC Power splitter. Provides convenient termination / distribution of serial control and 24VDC power to up to six locations.	\$210.00
DDI-REL-8	8 Control Relays (NO-NC) with remote serial control. Provides remote On/Off of microwave or other options.	\$480.00
DDI-MUX-6	Control Signal Multiplexer. Allows up to 5 DDI Controllers on one RS-485 network.	\$1,125.00

Projector		
Model #	Anti-Theft / Theft Deterrent Projector Ceiling Mount Systems	List
AT-PCM-###	Anti-Theft Projector Ceiling Mount System Includes active top pan, 6" pole and projector mounting system. Provides high output alarm (120db) with vibration sensor, projector presence sensor, electronic key, relay outputs and mechanical deterrence. Specify make and model # of projector and lens. 110V/220V	\$985.00
AT-LAN-PCM	AntiTheft Mount with Ethernet I/O port and Monitoring software package.	\$1,310.00
AT-KEY	Duplicate Key for Anti-Theft Projector Mount Specify Serial number of AT-PCM.	\$45.00
SC-PCM-###	Security Cage/Projector Ceiling Mount - cage surrounds projector for theft deterrence and physical protection. Includes 20° tilt, 10° pitch, 180° yaw. Specify make and model # of projector and lens.	\$643.00
Model #	Motorized Rotation of Projected Image	List
MRCM	Motorized Rotating Ceiling Mount Rotates display product to two programmable show positions. Cannot be used on lift. 250 lb. capacity. Contact closure remote port. Requires 2" diameter pole and projector mount to complete system. 110V. Optional wall mounted remotes available.	\$1,850.00
PLMT-A1	Pole Mount Adjustable Pole 2 inch diameter, adjustable length of 1' to 2'.	\$115.00
PCM-2.0-###	Standard Projector Ceiling Mount. Provides 20° tilt, 10° pitch, 180° yaw with 250 Lb weight capacity. 2" diameter threaded flange. Specify projector make and model.	\$215.00
MRCM 220V	Motorized Rotating Ceiling Mount Rotates display product to two programmable show positions. Cannot be used on lift. 250 lb. capacity. Contact closure remote port. Requires 2" diameter pole and projector mount to complete system. 220V. Optional wall mounted remotes available.	\$1,850.00
iMRCM	Infinite Motorized Rotating Ceiling Mount Continuous rotation of flat panel displays. Cannot be used on lift. 250 lb. capacity. Contact closure remote port. Requires 2" diameter pole and projector mount to complete system. 360 degree rotation.	\$2,853.00
REM-IR-MRCM	Wireless Infrared Remote Control. Used with MRCM. Comes with 5 Volt Power Supply.	\$460.00
WPR-M01-W	Wall Plate Remote panel for MRCM. Single gang white.	\$75.00
WPR-M01-B	Wall Plate Remote panel for MRCM. Single gang black.	\$75.00
WPR-M01-S	Wall Plate Remote panel for MRCM. Single gang brushed steel .	\$75.00

REM-M19-RM	Rack mount Panel Remote wired control panel for MRCM. 1.75" x 19" EIA. Black	\$75.00
REM-M02-W	Locking Wall Plate Remote wired control panel for MRCM with security key lock. 2 gang, white	\$115.00
REM-M02-B	Locking Wall Plate Remote wired control panel for MRCM with security key lock. 2 gang, black	\$115.00
REM-M02-S	Locking Wall Plate Remote wired control panel for MRCM with security key lock. 2 gang, brushed steel	\$115.00
Model #	Projector Ceiling Mounts - traditional - lower components	List
PCMK-Flex-2.0	Flexible Projector Ceiling Mount Adjustable mounting arms and legs provide mounting of most projectors weighing 15 Lbs. and less. 20° tilt, 20° roll, 180° yaw. Includes 2" diameter threaded flange, ceiling plate and projector hardware kit.	\$240.00
PCMK-Flex-1.5	Flexible Projector Ceiling Mount Adjustable mounting arms and legs provide mounting of most projectors weighing 15 Lbs. and less. 20° tilt, 20° roll, 180° yaw. Includes 1.5" diameter threaded flange, ceiling plate and projector hardware kit.	\$240.00
PCMK-2.0-###	Knucklehead Ceiling Mount for Small projectors. Provides 20° tilt, 20° pitch, 180° yaw with 15 lb capacity. Available for certain models only. Specify make / model#. Packaged with Ceiling Plate and 2" diameter threaded flange.	\$215.00
PCMK-1.5-###	Knucklehead Ceiling Mount for Small projectors. Provides 20° tilt, 20° pitch, 180° yaw with 15 lb capacity. Available for certain models only. Specify make / model#. Packaged with Ceiling Plate and 1.5" diameter threaded flange.	\$215.00
PCM-2.0-###	Standard Projector Ceiling Mount. Provides 20° tilt, 10° pitch, 180° yaw with 250 Lb weight capacity. 2" diameter threaded flange. Specify projector make and model.	\$215.00
PCM-1.5-###	Standard Projector Ceiling Mount. Provides 20° tilt, 10° pitch, 180° yaw with 250 Lb weight capacity. 1.5" diameter threaded flange. Specify projector make and model.	\$215.00
LS100-PCM-###	Motorized Lens Shutter with Projector Ceiling Mount. Provides blocking light from video projectors. Includes stationary ceiling mount for 1.5" or 2.0" pole. Specify make & model projector and lens.	\$715.00
AT-PCM-###	Anti-Theft Projector Ceiling Mount System Includes active top pan, 6" pole and projector mounting system. Provides high output audible alarm (120db) with vibration sensor, projector presence sensor, electronic key, relay outputs and mechanical deterrence.	\$985.00
AT-LAN-PCM	AntiTheft Mount with Ethernet I/O port and Monitoring software package.	\$1,310.00

SC-PCM-###	Security Cage/Projector Ceiling Mount - cage surrounds projector for theft deterrence and physical protection. Includes 20° tilt, 10° pitch, 180° yaw. Specify make and model.	\$500.00
Model #	Projector Ceiling Mounts - traditional - middle components	List
PLMT-PP1	Pole Mount PowerPRO Provides Single 1G junction box on threaded collar for 2" pole. Includes 1) J-box with threaded conduit connection points for plenum applications.	\$250.00
PLMT-PP2	Pole Mount PowerPRO Provides Dual 1G junction box on threaded collar for 2" pole. Includes 2 J-boxes; one duplex for 110V AC power and one empty for signal connection.	\$284.00
RCM	Rotating Ceiling Mount. Manual rotation of display. Cannot be used on lift. Requires pole 2", PCM and PLMT-T / AA / U / C / CTP2X2 to complete system.	\$178.00
PS-Kit	Pole Stabilizing Kit Attaches to 2" pole to stabilize from three points of structural ceiling. Uses either wire rope, 3/8" threaded rod or 1" conduit supplied by installer.	\$178.00
PSV-Kit	Pole Stabilizing / Anti-Vibration Kit Attaches to 2" pole to stabilize from three points of structural ceiling. Includes Anti-Vibration mounting points. Uses either wire rope, 3/8" threaded rod or 1" conduit supplied by installer.	\$320.00
PLMT-A1	Pole Mount Adjustable Pole 2 inch diameter, adjustable length of 1' to 2'.	\$115.00
PLMT-A2	Pole Mount Adjustable Pole 2 inch diameter, adjustable length of 2' to 4'.	\$115.00
PLMT-A3	Pole Mount Adjustable Pole 2 inch diameter, adjustable length of 3' to 6'.	\$115.00
PLMT-A4	Pole Mount Adjustable Pole 2 inch diameter, adjustable length of 4' to 8'.	\$165.00
PLMT-TP-A1	Top Plate attached to Pole Mount Adjustable Pole Light duty 2 inch diameter, adjustable length of 1' to 2'. <i>40 pound weight capacity</i> . Requires PCM-2.0 or PCMK-2.0.	\$115.00
PLMT-TP-A2	Top Plate attached to Pole Mount Adjustable Pole Light duty 2 inch diameter, adjustable length of 2' to 4'. <i>40 pound weight capacity</i> . Requires PCM-2.0 or PCMK-2.0.	\$115.00
PLMT-TP-A3	Top Plate attached to Pole Mount Adjustable Pole Light Duty 2 inch diameter, adjustable length of 3' to 6'. <i>40 pound weight capacity</i> . Requires PCM-2.0 or PCMK-2.0.	\$115.00
PL-2.0-06	Six Inch Pole 2" diameter x 6" long.	\$26.00
PL-1.5-06	Six Inch Pole 1.5" diameter x 6" long.	\$26.00
PL-2.0 - SPEC	Fixed Pole Specific length 2" diameter. Specify length and add \$4.50 per foot up to 10'	\$26.00
PL-1.5 - SPEC	Fixed Pole Specific length 1.5" diameter specify length and add \$4.50 per foot up to 10'	\$26.00
PLMT-EX-2.0	Pole Mount Extender Female to Female threaded collar to allow two 2" poles to be extended.	\$26.00

2-15	2" to 1.5" reducer - allows PLMT-T / AA / U / C / CTP2X2 to be used with other manufacturers mounts (2" female to 1.5" male threads).	\$50.00
15-2	1.5" to 2" collar - allows DDI mounts to use a 1.5" pole (1.5" female to 2" male threads).	\$50.00
OS-4	Offset Mount Adapter 2" male to 2" female threaded coupler shifts stationary mounts 4" horizontally to avoid obstructions.	\$71.00
CTR-2-W	Ceiling Trim Ring Magnetic escutcheon ring for 2" pole. White finish.	\$25.00
CTR-2-B	Ceiling Trim Ring Magnetic escutcheon ring for 2" pole. Black finish.	\$25.00
CTR-2-P	Ceiling Trim Ring Magnetic escutcheon ring for 2" pole. Primer finish.	\$25.00
Model #	Projector Ceiling Mounts - traditional - upper components	List
CTP-2X2	Ceiling Tile Panel for stationary mounting of projectors and flat panel displays. Provides versatile mounting positions in 2 ft. X 2 ft. drop tile. 160 lb weight capacity. Requires 2" diameter pole and mount to complete system.	\$195.00
CTP-2X2 LD-2.0	Ceiling Tile Panel-Light Duty Provides stationary mounting of projectors. Provides versatile mounting positions in 2 ft. X 2 ft. drop tile. 50 lb. capacity. Requires 2" diameter pole and mount to complete system.	\$135.00
CTP-2X2 LD-1.5	Ceiling Tile Panel-Light Duty Provides stationary mounting of projectors. Provides versatile mounting positions in 2 ft. X 2 ft. drop tile. 50 lb. capacity. Requires 1.5" diameter pole and mount to complete system.	\$135.00
CTP-1X2 LD-2.0	Ceiling Tile Panel-Light Duty Provides stationary mounting of projectors. Provides versatile mounting positions directly above drop tile. 50 lb capacity. Requires 2" diameter pole and mount to complete system.	\$135.00
CTP-1X2 LD-1.5	Ceiling Tile Panel-Light Duty Provides stationary mounting of projectors. Provides versatile mounting positions directly above drop tile. 50 lb capacity. Requires 1.5" diameter pole and mount to complete system.	\$135.00
PLMT-T-2.0	Pole Mount Top Panel Mounting Panel with threaded collar for 2" pole. Attaches to structural ceiling. Requires pole and projector mount to complete system. Weight capacity 300 pounds.	\$71.00
PLMT-T-1.5	Pole Mount Top Panel Mounting Panel with threaded collar for 1.5" pole. Attaches to structural ceiling. Requires pole and projector mount to complete system. Weight capacity 300 pounds.	\$71.00
PLMT-VIT	Pole Mount Top Panel w/ Vibration Isolation Attaches to structural ceiling for isolation of 2" pole. Must be purchased with complete PLMT system with specified weight capacity.	\$135.00

PLMT-LD-2.0	Light Duty Mount Top Panel with threaded collar for 2" pole. Attaches to structural ceiling. Requires pole and PCM mounting adapter to complete system. Maximum weight capacity 40 lbs includes pole and PCM.	\$50.00
PLMT-LD-1.5	Light Duty Mount Top Panel with threaded collar for 1.5" pole. Attaches to structural ceiling. Requires pole and PCM mounting adapter to complete system. Maximum weight capacity 40 lbs includes pole and PCM.	\$50.00
MRCM	Motorized Rotating Ceiling Mount Rotates display product to two programmable show positions. Cannot be used on lift. 250 lb. capacity. Contact closure remote port. Requires 2" diameter pole and projector mount to complete system. 110V. Optional wall mounted remotes available.	\$1,850.00
MRCM 220V	Motorized Rotating Ceiling Mount Rotates display product to two programmable show positions. Cannot be used on lift. 250 lb. capacity. Contact closure remote port. Requires 2" diameter pole and projector mount to complete system. 220V. Optional wall mounted remotes available.	\$1,850.00
WPR-M01-W	Wall Plate Remote panel for MRCM. Single gang white.	\$75.00
WPR-M01-B	Wall Plate Remote panel for MRCM. Single gang black.	\$75.00
WPR-M01-S	Wall Plate Remote panel for MRCM. Single gang brushed steel .	\$75.00
REM-M19-RM	Rack mount Panel Remote wired control panel for MRCM. 1.75" x 19" EIA. Black	\$75.00
REM-M02-W	Locking Wall Plate Remote wired control panel for MRCM with security key lock. 2 gang, white	\$115.00
REM-M02-B	Locking Wall Plate Remote wired control panel for MRCM with security key lock. 2 gang, black	\$115.00
REM-M02-S	Locking Wall Plate Remote wired control panel for MRCM with security key lock. 2 gang, brushed steel	\$115.00
PLMT-AA	Pole Mount Angle Adapter Angled mounting panel with threaded collar for 2" pole. For cathedral style ceilings; 0° - 90°. Requires pole and PCM mounting adapter to complete system. 150# weight limit.	\$115.00
PLMT-U	Pole Mount for U-Channel Structural channel bracket with threaded collar for 2" pole. Requires U-Channel, pole and PCM mounting adapter to complete system. For projectors 30 lbs or less	\$63.00
PLMT-C	Pole Mount C-Clamp C-Clamp with threaded collar for 2" pole. Clamp attaches 2" pole to horizontal structural pipe. Requires pole and PCM mounting adapter to complete system.	\$63.00
PLMT-WA-8	Pole Mount Wall Arm Arm mounts to wall provided with 2" threaded collar. Mounts smaller projectors 8" from wall. Requires pole and PCM mounting adapter to complete system.	\$98.00

PLMT-WA-12	Pole Mount Wall Arm Arm mounts to wall provided with 2" threaded collar. Mounts smaller projectors 12" from wall. Requires pole and PCM mounting adapter to complete system.	\$98.00
CamPan-WM	Camera Panel Wall Mount Wall mounted camera panel for light-weight camera/pan/tilt. Provides tilt adjustment. 20 lb. capacity. Specify make & model of camera system.	\$215.00
Model #	Outdoor Projector Enclosure	List
PJE-1000	Projector Enclosure. All-metal, NEMA3R enclosure with optical glass viewing port and front hinged door with tamper resistant lock system. Integrated 8,000BTU sealed air conditioner with programmable digital thermostat and circulation fans (heater optional). RS-232 I/O for remote monitoring and control. Internal AVStack projector alignment mounting frame. Locking glide system for easy projector access. 110V. Designed for temperature range 32°-100° F. Powdercoat White Finish (other colors optional). Specify make/model of projector plus lens. Maximum proj dimension=9.9"H x 30.8"D x 22.9"W.	\$8,500.00
Model #	Sound Enclosures	List
SE-B1	Sound Enclosure for small sized video projectors. Maximum projector size: 19"W x 19"L x 11"V. Fits into 2' x 2' drop tile style ceilings to isolate cooling fan noise from viewers. Includes optical glass projection port, programmable cooling system and UL rated fire dampers. Requires PCM-### mount. 110V.	\$3,300.00
SE-B1 220V	Sound Enclosure for small sized video projectors. Maximum projector size: 19"W x 19"L x 11"V. Fits into 2' x 2' drop tile style ceilings to isolate cooling fan noise from viewers. Includes optical glass projection port, programmable cooling system and UL rated fire dampers. Requires PCM-### mount. 110V/220V. OPT15 enhanced electronics available.	\$3,300.00
SE-B2	Sound Enclosure for mid-sized video projectors. Maximum projector size: 19"W x 31"L x 11"V. Fits into 2' x 3' drop tile style ceilings to isolate cooling fan noise from viewers. Includes optical glass projection port, programmable cooling system and UL rated fire dampers. Requires PCM-### mount. 110V. OPT15 enhanced electronics available.	\$3,805.00
SE-B2 220V	Sound Enclosure for mid-sized video projectors. Maximum projector size: 19"W x 31"L x 11"V. Fits into 2' x 3' drop tile style ceilings to isolate cooling fan noise from viewers. Includes optical glass projection port, programmable cooling system and UL rated fire dampers. Requires PCM-### mount. 220V. OPT15 enhanced electronics available.	\$3,805.00

SE-B3	Sound Enclosure for video projectors. Maximum projector size: 23"W x 27"L x 11"V. To isolate cooling fan noise from viewers. Includes optical glass projection port, programmable cooling system and UL rated fire dampers. Requires PCM-### mount. 110V. OPT15 enhanced electronics available.	\$4,156.00
SE-B3 220V	Sound Enclosure for video projectors. Maximum projector size: 23"W x 27"L x 11"V. To isolate cooling fan noise from viewers. Includes optical glass projection port, programmable cooling system and UL rated fire dampers. Requires PCM-### mount. 220V. OPT15 enhanced electronics available.	\$4,156.00
SE-BXL	Sound Enclosure for mid-sized video projectors. Maximum projector size: 29"W x 40"L x 15"D. Fits into drop tile style ceilings to isolate cooling fan noise from viewers. Includes optical glass projection port, programmable cooling system, OPT15 and UL rated fire dampers. Requires PCM-## mount. 110V	\$7,130.00
SE-BXL 220V	Sound Enclosure for mid-sized video projectors. Maximum projector size: 29"W x 40"L x 15"D. Fits into drop tile style ceilings to isolate cooling fan noise from viewers. Includes optical glass projection port, programmable cooling system, OPT15 and UL rated fire dampers. Requires PCM-### mount. 220V	\$7,130.00
SE-B5s	Sound Enclosure for Soffit Application no projector lift. Maximum projector size: 22"W x 25"D x 10"H. Designed to integrate into a soffit with Intake and Exhaust ports on the sides. Includes optical glass projection port. Requires PCM-### mount. 110V. RS-232 and Remote Temperature Probe included.	\$4,270.00
SE-B5s 220V	Sound Enclosure for Soffit Application no projector lift. Maximum projector size: 22"W x 25"D x 10"H. Designed to integrate into a soffit with Intake and Exhaust ports on the sides. Includes optical glass projection port. Requires PCM-### mount. 220V. RS-232 and Remote Temperature Probe included.	\$4,270.00
SE-B6s	Sound Enclosure for Soffit Application and LCD-104 (not included) projector lift. Maximum projector size: 22"W x 27"D x 14"H. Designed to integrate into a soffit with Intake and Exhaust ports on the sides. Includes optical glass projection port. Requires LCD-104 or PCM-### mount. 110V. RS-232 and Remote Temperature Probe included.	\$4,270.00
SE-B6s 220V	Sound Enclosure for Soffit Application and LCD-104 (not included) projector lift. Maximum projector size: 22"W x 27"D x 14"H. Designed to integrate into a soffit with Intake and Exhaust ports on the sides. Includes optical glass projection port. Requires LCD-104 or PCM-### mount. 220V. RS-232 and Remote Temperature Probe included.	\$4,270.00

SE-B10s	Sound Enclosure for Soffit Application and DL3W-12 (not included) projector lift. Maximum projector size: 30"W x 48"D x 20"H. Designed to integrate into a soffit with Intake and Exhaust ports on the sides. Includes optical glass projection port and RS-232 com port. Requires DL3W-12 or PCM-### mount. 110V. OPT15 enhanced electronics included.	\$8,559.00
SE-B10s 220V	Sound Enclosure for Soffit Application and DL3W-12 (not included) projector lift. Maximum projector size: 30"W x 48"D x 20"H. Designed to integrate into a soffit with Intake and Exhaust ports on the sides. Includes optical glass projection port and RS-232 com port. Requires DL3W-12 or PCM-### mount. 220V. OPT15 enhanced electronics included.	\$8,559.00
S.E.R.F 110V	Projector Sound Enclosure with Remote Fans. For Soffit Applications. Overall dimensions 37.90"W x 34"D x 20"H. Maximum projector size, including lens: 22"W x 30"D x 10"H. Designed to integrate into a soffit with intake and exhaust ports on the sides. Remote fan kit included: (2) In-line, variable speed remote fans with controllers, (2) 25' insulated flex duct and fittings. Programmable digital thermostat. Optical glass projection port. Hinged, locking bottom door for service. 110V. RS-232 I/O Port and Remote Temperature Probe included.	\$8,418.00
S.E.R.F 220V	Projector Sound Enclosure with Remote Fans. For Soffit Applications. Overall dimensions 37.90"W x 34"D x 20"H. Maximum projector size, including lens: 22"W x 30"D x 10"H. Designed to integrate into a soffit with intake and exhaust ports on the sides. Remote fan kit included: (2) In-line, variable speed remote fans with controllers, (2) 25' insulated flex duct and fittings. Programmable digital thermostat. Optical glass projection port. Hinged, locking bottom door for service. 220V. RS-232 I/O Port and Remote Temperature Probe included.	\$8,418.00
SE-TR 2X2	Trim Ring for Sound Enclosure - attaches to lower cavity - extends 1.5" from side of enclosure to hid any seams around enclosure for 2' x 2' size.	\$150.00
SE-TR 2X3	Trim Ring for Sound Enclosure - attaches to lower cavity - extends 1.5" from side of enclosure to hid any seams around enclosure for 2' x 3' size.	\$150.00
SE-TR B3	Trim Ring for Sound Enclosure - for SE-B3 attaches to lower cavity - extends 1.5" from side of enclosure to hid any seams around enclosure.	\$150.00
SE-TR BXL	Trim Ring for Sound Enclosure - for SE-BXL attaches to lower cavity - extends 1.5" from side of enclosure to hid any seams around enclosure.	\$150.00

Model #	Projector Lens Shutter	List
LS-100	Motorized Lens Shutter for blocking light from video projectors. Designed to attach to the projector or AVStack with double-stick tape in temporary applications. Specify make & model projector and lens.	\$500.00
LS100-PCM-###	Motorized Lens Shutter with Projector Ceiling Mount. Provides blocking light from video projectors. Includes stationary ceiling mount for 1.5" or 2.0" pole. Specify make & model projector and lens.	\$715.00

PROJECTOR LIFTS		
Model #	IBL Series Projector Lifts (35 # capacity)	List
IBL-1522	Small projector lift with 39" of maximum travel designed to fit within 16" on-center floor joists. Provided standard with adjustable plenum enclosure, ceiling closure frame, handheld wired remote and dry contact closure interface, maximum projector dimensions: 12.5" w X 18.5" X 11" h, 35 lb capacity. Includes Universal Projector Mount. 110V	\$2,475.00
IBL-1522 220V	Small projector lift with 39" of maximum travel designed to fit within 16" on-center floor joists. Provided standard with adjustable plenum enclosure, ceiling closure frame, handheld wired remote and dry contact closure interface, maximum projector dimensions: 12.5 inches wide X 18.5 inches long X 11 inches high. 35 lb capacity. Includes Universal Projector Mount. 220V	\$2,475.00
IBL 2424	Small projector lift with 39" of maximum travel designed to fit within 2'x 2' ceiling tile. Provided standard with adjustable plenum enclosure, ceiling closure frame, handheld wired remote and dry contact closure interface, Maximum projector size: 19" x 19" (including lens). 35 lb capacity. Includes Universal Projector Mount. 110V	\$2,475.00
IBL 6060 220V	Small projector lift with 39" of maximum travel designed to fit within 60cm x 60cm ceiling tile. Provided standard with adjustable plenum enclosure, ceiling closure frame, handheld wired remote and dry contact closure interface, 35 lb capacity. Includes Universal Projector Mount. 220V	\$2,475.00
Model #	USD Series Projector Lifts (40 # capacity)	List
USD-100	Small projector UPlift with 10.5" of vertical travel. Provided standard with handheld wired remote and dry contact closure interface, Max projector size 14"W x 14.5"L. 40 lb weight capacity (including projector and table closure panel). 110V	\$1,575.00
USD-100	Small projector UPlift with 10.5" of vertical travel. Provided standard with handheld wired remote and dry contact closure interface, Max projector size 14"W x 14.5"L. 40 lb weight capacity (including projector and table closure panel). 220V	\$1,575.00
USD-LID	Closure Panel fixed top closure panel for USD-100. Max projector height 7".	\$215.00
Model #	DataLite LCD Series Projector Lifts (80 Lb capacity)	List
LCD-104	DataLite projector lift with 4 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$2,790.00

LCD-104 220V	DataLite projector lift with 4 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$2,790.00
LCD-104 W/ RS-232	DataLite projector lift with 4 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$3,085.00
LCD-104 220V W/ RS- 232	DataLite projector lift with 4 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$3,085.00
LCD-105	DataLite projector lift with 5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V.	\$3,020.00
LCD-105 220V	DataLite projector lift with 5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$3,020.00
LCD-105 W/ RS-232	DataLite projector lift with 5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$3,314.00
LCD-105 220V W/ RS- 232	DataLite projector lift with 5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$3,314.00
LCD-106	DataLite projector lift with 6 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$3,250.00
LCD-106 220V	DataLite projector lift with 6 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$3,250.00
LCD-106 W/ RS-232	DataLite projector lift with 6 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$3,550.00
LCD-106 220V W/ RS- 232	DataLite projector lift with 6 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$3,550.00
LCD-107	DataLite projector lift with 7 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$3,480.00

LCD-107 220V	DataLite projector lift with 7 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$3,480.00
LCD-107 W/ RS-232	DataLite projector lift with 7 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$3,778.00
LCD-107 220V W/ RS- 232	DataLite projector lift with 7 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$3,778.00
Model #	DataLift DL3B Series Projector Lifts (160 # capacity)	List
DL3B-7.5	DataLift projector lift with 7.5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$3,527.00
DL3B-7.5 220V	DataLift projector lift with 7.5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$3,527.00
DL3B-7.5 W/ RS-232	DataLift projector lift with 7.5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$3,821.00
DL3B-7.5 220V W/ RS- 232	DataLift projector lift with 7.5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$3,821.00
DL3B-9.5	DataLift projector lift with 9.5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$3,757.00
DL3B-9.5 220V	DataLift projector lift with 9.5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$3,757.00
DL3B-9.5 W/ RS-232	DataLift projector lift with 9.5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$4,057.00
DL3B-9.5 220V W/ RS- 232	DataLift projector lift with 9.5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$4,057.00

DL3B-11	DataLift projector lift with 11.0 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$3,988.00
DL3B-11 220V	DataLift projector lift with 11.0 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$3,988.00
DL3B-11 W/ RS-232	DataLift projector lift with 11.0 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$4,285.00
DL3B-11 220V W/ RS- 232	DataLift projector lift with 11.0 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$4,285.00
DL3B-12.5	DataLift projector lift with 12.5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$4,218.00
DL3B-12.5 220V	DataLift projector lift with 12.5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$4,218.00
DL3B-12.5 W/ RS-232	DataLift projector lift with 12.5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$4,514.00
DL3B-12.5 220V W/ RS- 232	DataLift projector lift with 12.5 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$4,514.00
DL3B-14	DataLift projector lift with 14.0 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$4,449.00
DL3B-14 220V	DataLift projector lift with 14.0 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$4,449.00
DL3B-14 W/ RS-232	DataLift projector lift with 14.0 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$4,742.00
DL3B-14 220V W/ RS- 232	DataLift projector lift with 14.0 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$4,742.00

Model #	DataWide DL3W Projector Lifts (400 # capacity)	List
DL3W-12	DataWide projector lift with 12 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$4,295.00
DL3W-12 220V	DataWide projector lift with 12 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$4,295.00
DL3W-12 W/ RS-232	DataWide projector lift with 12 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$4,592.00
DL3W-12 220V W/ RS-232	DataWide projector lift with 12 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$4,592.00
DL3W-14	DataWide projector lift with 14 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$4,625.00
DL3W-14 220V	DataWide projector lift with 14 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$4,625.00
DL3W-14 W/ RS-232	DataWide projector lift with 14 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$4,921.00
DL3W-14 220V W/ RS-232	DataWide projector lift with 14 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$4,921.00
DL3W-16	DataWide projector lift with 16 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$4,950.00
DL3W-16 220V	DataWide projector lift with 16 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$4,950.00
DL3W-16 W/ RS-232	DataWide projector lift with 16 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$5,250.00

DL3W-16 220V W/ RS- 232	DataWide projector lift with 16 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$5,250.00
DL3W-18	DataWide projector lift with 18 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$5,275.00
DL3W-18 220V	DataWide projector lift with 18 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$5,275.00
DL3W-18 W/ RS-232	DataWide projector lift with 18 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$5,571.00
DL3W-18 220V W/ RS- 232	DataWide projector lift with 18 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$5,571.00
DL3W-20	DataWide projector lift with 20 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$5,920.00
DL3W-20 220V	DataWide projector lift with 20 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$5,920.00
DL3W-20 W/ RS-232	DataWide projector lift with 20 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$6,214.00
DL3W-20 220V W/ RS- 232	DataWide projector lift with 20 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$6,214.00
DL3W-24	DataWide projector lift with 24 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$6,565.00
DL3W-24 220V	DataWide projector lift with 24 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$6,565.00
DL3W-24 W/ RS-232	DataWide projector lift with 24 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$6,864.00

DL3W-24 220V W/ RS- 232	DataWide projector lift with 24 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$6,864.00
DL3W-28	DataWide projector lift with 28 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V	\$7,535.00
DL3W-28 220V	DataWide projector lift with 28 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V	\$7,535.00
DL3W-28 W/ RS-232	DataWide projector lift with 28 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 110V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$7,828.00
DL3W-28 220V W/ RS- 232	DataWide projector lift with 28 feet of travel. Provided with handheld wired remote and dry contact closure interface standard. 220V. RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$7,828.00
Model #	Motorized Rotation Option for Projector Lift	List
EMRCM	Electronic Motorized Rotating Ceiling Mount - Provides rotational positioning of a projector in addition to elevation. Includes program utility software for programming up to 9 preset locations to allow multiple vertical and rotational show positions. Must use third party RS232 control system. Weight capacity of 100 lbs. 110V. Specify lift (LCD or DL-3W series ONLY) and projector model.	\$2,785.00
EMRCM 220V	Electronic Motorized Rotating Ceiling Mount - Provides rotational positioning of a projector in addition to elevation. Includes program utility software for programming up to 9 preset locations to allow multiple vertical and rotational show positions. Must use third party RS232 control system. Weight capacity of 100 lbs. 110V. Specify lift (LCD or DL-3W series ONLY) and projector model.	\$2,785.00
Model #	Projector Lift Options	List
###	Mounting Adapter interface for projector. Must specify make and model number of projector and lens if projector offers options.	\$218.00
LIFT-Flex	Flexible Projector LIFT Mount Adjustable mounting arms and legs provide mounting of most projectors weighing 35 Lbs. and less.	\$240.00
OPT-1	Ceiling Closure Frame - Used with drywall or wood ceilings. Provides 2" trim finish for projector opening. Spring loaded and fully adjustable. Note: EBR is recommended for installations with restricted access.	\$488.00

OPT-1L	Lipless Ceiling Closure Frame - Provides minimal seam around projector opening for drywall or wood ceilings. Spring loaded and fully adjustable. Note: EBR is recommended for installations with restricted access.	\$488.00
OPT-1L-2X2	2' x 2' Lipless Ceiling Closure Frame for LCD-100 series only - Maximum projector size: 19" x 19" (including lens). Provides minimal seam around projector opening for drywall or wood ceilings. Spring loaded and fully adjustable. Note: EBR is recommended for installations with restricted access.	\$488.00
EBR	Emergency Brake Release. Lowers lift for service access. Recommended when access to a retracted lift is restricted i.e., drywall. <i>Must be purchased at the same time as the lift.</i>	\$215.00
OPT-3	Plenum Rated Housing With Closure Frame - Provides enclosure to meet most air plenum ceiling area needs. 2" trim finish for projector opening. Includes ceiling closure, spring loaded and fully adjustable.	\$1,266.00
OPT-3L	Plenum Rated Housing With Lipless Closure Frame - Provides enclosure to meet most air plenum ceiling area needs. Provides minimal seam around projector opening. Includes ceiling closure, spring loaded and fully adjustable.	\$1,266.00
OPT-3L-2x2	2' x 2' Plenum Rated Housing With Lipless Closure Frame for LCD-100 series only - Maximum projector size: 19" x 19" (including lens). Provides enclosure to meet most air plenum ceiling area needs. Provides minimal seam around projector opening. Includes ceiling closure, spring loaded and fully adjustable.	\$1,266.00
OPT-4	Non-Plenum Rated Housing With Closure Frame - Support framework and closure frame for drop tile ceilings with non-plenum requirements. 2" trim finish for projector opening. Includes ceiling closure, spring loaded and fully adjustable.	\$748.00
OPT-4L	Non-Plenum Rated Housing With Lipless Closure Frame - Support framework and closure frame for drop tile ceilings with non-plenum requirements. Provides minimal seam around projector opening. Includes ceiling closure, spring loaded and fully adjustable.	\$748.00
OPT-4L-2x2	2' x 2' Non-Plenum Rated Housing With Lipless Closure Frame for LCD-100 series only - Maximum projector size: 19" x 19" (including lens). Support framework and closure frame for drop tile ceilings with non-plenum requirements. Provides minimal seam around projector opening. Includes ceiling closure, spring loaded and fully adjustable.	\$748.00
OPT-5	Bomb Bay Door ceiling closure system - Provides support framework and dual opening doors for non-plenum applications.	\$1,421.00

OPT-9	RS-232 Serial control interface - allows for unlimited show positions when using a third party control system (Crestron/AMX).	\$300.00
OPT-11-A	Cable Pre Wire Prewire of any LCD-100 or DL-3B series projector lift with control, signal and power cabling. (Not for IBL series)	\$572.00
OPT-11-B	Cable Pre Wire Prewire of DL3W series projector lift with control, signal and power cabling.	\$1,145.00
PCS-02	Power Current Sensor Ultra sensitive current sensing of projectors and display panels. 110V. Provides contact closure out.	\$111.00
REM-IR	Wireless Infrared Remote control. May be used with any motorized DDI product.	\$285.00
REM-RF	Wireless Radio Frequency Remote control May be used with any motorized DDI product.	\$357.00
WPR-L01-W	Wall Plate Remote panel for all PlasmaLifts. Single gang white. 3 button - Up, Down, Stop & programming.	\$75.00
WPR-L01-B	Wall Plate Remote panel for all PlasmaLifts. Single gang black. 3 button - Up, Down, Stop & programming.	\$75.00
WPR-L01-S	Wall Plate Remote panel for all PlasmaLifts. Single gang brushed steel. 3 button - Up, Down, Stop & programming.	\$75.00
REM-L19-RM	Rack mount Panel Remote wired control panel for all PlasmaLifts. 1.75" x 19" EIA. Black. 3 button - Up, Down, Stop & programming.	\$75.00
REM-L02-W	Locking Wall Plate Remote wired control panel with security key lock. 4" x 4". Double gang, white. 3 button - Up, Down, Stop & programming.	\$115.00
REM-L02-B	Locking Wall Plate Remote wired control panel with security key lock. 4" x 4". Double gang, black. 3 button - Up, Down, Stop & programming.	\$115.00
REM-L02-S	Locking Wall Plate Remote wired control panel with security key lock. 4" x 4". Double gang, brushed steel. 3 button - Up, Down, Stop & programming.	\$115.00
SPK-LCD-S 110V	Spare Parts Kit - Spare parts for LCD, RS-232 Controlled lifts. Comes with (1) motor, (1) control box, (1) slot sensor, (1) slot sensor wheel, (1) wire harness and (1) limit switch. (110V)	\$1,286.00
SPK-LCD-S 220V	Spare Parts Kit - Spare parts for LCD, RS-232 Controlled lifts. Comes with (1) motor, (1) control box, (1) slot sensor, (1) slot sensor wheel, (1) wire harness and (1) limit switch. (220V)	\$1,286.00
SPK-LCD 110V	Spare Parts Kit - Spare parts for LCD lifts. Comes with (1) motor, (1) control box, (1) slot sensor, (1) slot sensor wheel, (1) wire harness and (1) limit switch. (110V)	\$1,286.00
SPK-LCD 220V	Spare Parts Kit - Spare parts for LCD lifts. Comes with (1) motor, (1) control box, (1) slot sensor, (1) slot sensor wheel, (1) wire harness and (1) limit switch. (220V)	\$1,286.00

SPK-DL3B-S 110V	Spare Parts Kit - Spare parts for DL3B, RS-232 Controlled lifts. Comes with (1) motor, (1) control box, (1) slot sensor, (1) slot sensor wheel, (1) wire harness and (1) limit switch. (110V)	\$1,286.00
SPK-DL3B-S 220V	Spare Parts Kit - Spare parts for DL3B, RS-232 Controlled lifts. Comes with (1) motor, (1) control box, (1) slot sensor, (1) slot sensor wheel, (1) wire harness and (1) limit switch. (220V)	\$1,286.00
SPK-DL3B 110V	Spare Parts Kit - Spare parts for DL3B lifts. Comes with (1) motor, (1) control box, (1) slot sensor, (1) slot sensor wheel, (1) wire harness and (1) limit switch. (110V)	\$1,286.00
SPK-DL3B 220V	Spare Parts Kit - Spare parts for DL3B lifts. Comes with (1) motor, (1) control box, (1) slot sensor, (1) slot sensor wheel, (1) wire harness and (1) limit switch. (220V)	\$1,286.00
SPK-SW 110V	Spare Parts Kit - Spare parts for DL3W, RS-232 Controlled lifts. Comes with (1) motor, (1) splitter box, (1) control box, (1) slot sensor, (1) slot sensor wheel, (1) wire harness and (1) limit switch. (110V)	\$1,357.00
SPK-SW 220V	Spare Parts Kit - Spare parts for DL3W, RS-232 Controlled lifts. Comes with (1) motor, (1) splitter box, (1) control box, (1) slot sensor, (1) slot sensor wheel, (1) wire harness and (1) limit switch. (220V)	\$1,643.00
SPK-WD 110V	Spare Parts Kit - Spare parts for DL3W lifts. Comes with (1) motor, (1) splitter box, (1) control box, (1) slot sensor, (1) slot sensor wheel, (1) wire harness and (1) limit switch. (110V)	\$1,643.00
SPK-WD 220V	Spare Parts Kit - Spare parts for DL3W lifts. Comes with (1) motor, (1) splitter box, (1) control box, (1) slot sensor, (1) slot sensor wheel, (1) wire harness and (1) limit switch. (220V)	\$1,643.00
ECB	Lift Control Box	\$455.00
Model #	Staging Products- Projector Stackers	List
AVS-MINI- ###	AVStack Mini Projector mounting frame with three point adjustment for alignment and stacking/flying. Square steel framework with black powder coat finish. Built to accommodate smaller (50 Lb max) venue projectors. Specify Make / Model # of projector.	\$840.00
AVS-###	AVStack Projector mounting frame with three point adjustment for alignment and stacking/flying. 2" tube, easy to attach to truss. Aluminum frame. Built to accommodate most mid-large venue projectors. Specify Make / Model # of projector.	\$1,465.00
AVSC	AVStack Clamps Set of four to attach 2 units together. Not required for AVStack-Mini	\$153.00
PG-01	ProGate Fly AVStacks from truss and provides additional tilt, pitch, and yaw adjustments. Specify projector make and model.	\$2,570.00

Model #	Vogels Short Throw Projector Mounts	List
PPS 500	Short throw projector mount. Includes universal projector mount. Max weight 33#.Adjusts 23-36". Fully adjustable.	\$621.00
PPS 800	Short throw projector mount. Includes universal projector mount. Max weight 33#.Adjusts 35-60". Fully adjustable.	
PPS 801	Short throw swivel arm projector mount. Includes universal projector mount. Max weight 33#.Adjusts 40-61". Fully adjustable.	\$721.00
PPSA 200	Security Cage for PPS 801. Lock included. 9.9" H X 18.3" W X 15.7" D.	\$567.00

Model #	Pump Topper	List
DSPT-2400	Pump Topper Digital Signage Solution. Aluminum construction NEMA3R enclosure. Two keyed, locking, hinged doors with ¼" anti glare poly carbonate viewing ports. Integrated components: (2) 24" WUXGA 16x9 LCD monitors, (2) 50W 8ohm weatherproof audio speakers, AdEdge media server, audio amplifier, broadband antenna, 2000BTU air conditioning and heating system. Programmable digital thermostat with RS-232 I/O for remote monitoring and control. Temperature range -20° to 115° F. Exterior powdercoat white finish. 110V, 20A.	\$8,600.00
Model #	Specialized Connectors	List
P20	Stereo Terminal Isolated 3.5mm to Screw Down Terminal	\$10.30
4-40	S-Video BreakThrough S-Video chassis mount to (2) BNC female - 1 to 24 quantity	\$19.50
4-40	S-Video BreakThrough S-Video chassis mount to (2) BNC female - 25 to 49 quantity	\$19.50
4-40	S-Video BreakThrough S-Video chassis mount to (2) BNC female - 50 to 99 quantity	\$19.50
4-40	S-Video BreakThrough S-Video chassis mount to (2) BNC female - 100+ quantity	\$19.50
15-50	15 Pin BreakThrough HD15p female chassis mount to (5) BNC female - 1 to 24 quantity	\$48.00
15-50	15 Pin BreakThrough HD15p female chassis mount to (5) BNC female- 25 to 49 quantity	\$48.00
15-50	15 Pin BreakThrough HD15p female chassis mount to (5) BNC female- 50 to 99 quantity	\$48.00
15-50	15 Pin BreakThrough 15PHD chassis to (5) BNC - 100+ quantity	\$48.00
PCS-02	Power Current Sensor for projectors and Plasma Displays, 110V only	\$111.00

Ultra Bright & High Bright LCD Monitors		
Model #	High Bright LCD Monitor- 24"	List
HB-N2410	SunView 24" Highbright LCD. 1500 NITS maximum light output 24" diagonal viewable area, 3000:1 contrast ratio, 1900 x 1200 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 110V/4A or 220V/2A. Day light viewable 32" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), DVI-D. Requires PE-UB-AC- Enclosure.	\$6,900.00
PE-HB-AC-24P/L	24" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 2,500 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/2.5 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$6,993.00
Model #	Ultra Bright LCD Monitor- 24"	List
UB-N2410	SunView 24" Ultrabright LCD. 2500 NITS maximum light output 24" diagonal viewable area, 3000:1 contrast ratio, 1900 x 1200 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 110V/7A or 220V/3.5A. Day light viewable 32" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), DVI-D. Requires PE-UB-AC- Enclosure.	\$8,317.00
PE-UB-AC-24P/L	24" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 4,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/4 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$7,136.00
Model #	Options for 24" High Bright / Ultra Bright LCD Monitor	List
OPT-OTS-24	Touchscreen for 24" Panel Enclosure - Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 7 year or 60 Million actuations life, 92%-100% transmission accuracy, no drift, vandal proof.	\$2,017.00

PE-Ped-24-P/L	Pedestal for PE-AC-24 with base - same dimensional as enclosure accessories to your specification. Heavy gauge steel construction, access door, floor base. Specify required height. Complies with ADA Requirements.	\$335.00
OPT-Heat	Heating Sub System Provides heating to any PE and PE-AC Panel Enclosure. Designed to elevate interior temperature up to panel's proper operating range. Extends lower temp range to sub-zero.	\$743.00
Model #	High Bright LCD Monitor- 32"	List
HB-N3210	SunView 32" Highbright LCD. 1500 NITS maximum light output 32" diagonal viewable area, 800:1 contrast ratio, 1366 x 768 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 110V/6A or 220V/3A. Day light viewable 32" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), DVI-D. Requires PE-UB-AC- Enclosure.	\$8,253.00
PE-HB-AC-32P/L	32" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 3,500 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/3.5 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$7,679.00
Model #	Ultra Bright LCD Monitor- 32"	List
UB-N3210	SunView 32" Ultrabright LCD. 2500 NITS maximum light output 32" diagonal viewable area, 800:1 contrast ratio, 1366 x 768 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 110V/11A or 220V/5.5A. Day light viewable 32" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), DVI-D. Requires PE-UB-AC- Enclosure.	\$10,261.00
PE-UB-AC-32P/L	32" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 5,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/5 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$7,850.00

Model #	Options for 32" High Bright / Ultra Bright LCD Monitor	List
OPT-OTS-32	Touchscreen for 32" Panel Enclosure - Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 7 year or 60 Million actuations life, 92%-100% transmission accuracy, no drift, vandal proof.	\$2,589.00
PE-Ped-32-P/L	Pedestal for PE-AC-32 with base - same dimensional as enclosure accessories to your specification. Heavy gauge steel construction, access door, floor base. Specify required height. Complies with ADA Requirements.	\$350.00
OPT-Heat	Heating Sub System Provides heating to any PE and PE-AC Panel Enclosure. Designed to elevate interior temperature up to panel's proper operating range. Extends lower temp range to sub-zero.	\$743.00
Model #	High Bright LCD Monitor- 40"	List
HB-N4020	SunView 40" Highbright LCD. 1500 NITS maximum light output 40" diagonal viewable area, 2,000:1 contrast ratio, 1366 x 768 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 110V/7A or 220V/3.5A. Day light viewable 40" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), HDMI. Requires PE-UB- AC- Enclosure.	\$11,473.00
PE-HB-AC-40P/L	40" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 4,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/4 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$7,900.00
Model #	Ultra Bright LCD Monitor- 40"	List
UB-N4020	SunView 40" Ultrabright LCD. 2500 NITS maximum light output 40" diagonal viewable area, 2,000:1 contrast ratio, 1366 x 768 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 110V/12A or 220V/6A. Day light viewable 40" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), HDMI. Requires PE-UB- AC- Enclosure.	\$13,111.00

PE-UB-AC-40P/L	40" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 6,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/6 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$8,565.00
Model #	Options for 40" High Bright / Ultra Bright LCD Monitor	List
OPT-OTS-40	Touchscreen for 40" Panel Enclosure - Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 7 year or 60 Million actuations life, 92%-100% transmission accuracy, no drift, vandal proof.	\$3,303.00
PE-Ped-40-P/L	Pedestal for PE-AC-40 with base - same dimensional as enclosure accessories to your specification. Heavy gauge steel construction, access door, floor base. Specify required height. Complies with ADA Requirements.	\$372.00
OPT-Heat	Heating Sub System Provides heating to any PE and PE-AC Panel Enclosure. Designed to elevate interior temperature up to panel's proper operating range. Extends lower temp range to sub-zero.	\$743.00
Model #	High Bright LCD Monitor- 46"	List
HB-N4620	SunView 46" Highbright LCD. 1500 NITS maximum light output 46" diagonal viewable area, 2,000:1 contrast ratio, 1366 x 768 resolution, LED backlight life 50,000 hours at 50% brightness, 110V/10A or 220V/5A. Day light viewable 46" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), HDMI. Requires PE-UB- AC- Enclosure.	\$12,461.00
PE-HB-AC-46P/L	46" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 5,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/5 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$8,758.00

Model #	Ultra Bright LCD Monitor- 46"	List
UB-N4620	SunView 46" Ultrabright LCD. 2500 NITS maximum light output 46" diagonal viewable area, 2,000:1 contrast ratio, 1366 x 768 resolution, LED backlight life 50,000 hours at 50% brightness, 220V/8A only. Day light viewable 46" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), HDMI. Requires PE-UB- AC- Enclosure.	\$15,769.00
PE-UB-AC-46P/L	46" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 8,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/8 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$9,186.00
Model #	Options for 46" High Bright / Ultra Bright LCD Monitor	List
OPT-OTS-46	Touchscreen for 46" Panel Enclosure - Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 7 year or 60 Million actuations life, 92%-100% transmission accuracy, no drift, vandal proof.	\$3,939.00
PE-Ped-46-P/L	Pedestal for PE-AC-46 with base - same dimensional as enclosure accessories to your specification. Heavy gauge steel construction, access door, floor base. Specify required height. Complies with ADA Requirements.	\$435.00
OPT-Heat	Heating Sub System Provides heating to any PE and PE-AC Panel Enclosure. Designed to elevate interior temperature up to panel's proper operating range. Extends lower temp range to sub-zero.	\$743.00
Model #	High Bright LCD Monitor- 52"	List
HB-N5220	SunView 52" Highbright LCD. 1500 NITS maximum light output 52" diagonal viewable area, 2,000:1 contrast ratio, 1920 x 1080 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 110 V/13A or 220V/6.5A. Day light viewable 52" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), HDMI. Requires PE-UB- AC- Enclosure.	\$16,288.00

PE-HB-AC-52P/L	52" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 7,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/7 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$9,236.00
Model #	Ultra Bright LCD Monitor- 52"	List
UB-N5220	SunView 52" Ultrabright LCD. 2500 NITS maximum light output 52" diagonal viewable area, 2,000:1 contrast ratio, 1920 x 1080 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 220V/11A only. Day light viewable 52" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), HDMI. Requires PE-UB-AC- Enclosure.	\$20,543.00
PE-UB-AC-52P/L	52" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 11,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/11 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$9,900.00
Model #	Options for 52" High Bright / Ultra Bright LCD Monitor	List
OPT-OTS-52	Touchscreen for 52" Panel Enclosure - Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 7 year or 60 Million actuations life, 92%-100% transmission accuracy, no drift, vandal proof.	\$4,357.00
PE-Ped-52-P/L	Pedestal for PE-AC-52 with base - same dimensional as enclosure accessories to your specification. Heavy gauge steel construction, access door, floor base. Specify required height. Complies with ADA Requirements.	\$507.00
OPT-Heat	Heating Sub System Provides heating to any PE and PE-AC Panel Enclosure. Designed to elevate interior temperature up to panel's proper operating range. Extends lower temp range to sub-zero.	\$743.00

Model #	High Bright LCD Monitor- 57"	List
HB-N5720	SunView 57" Highbright LCD. 1500 NITS maximum light output 57" diagonal viewable area, 1800:1 contrast ratio, 1920 x 1080 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 220V/7A only. Day light viewable 57" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), DVI-D. Requires PE-UB- AC-Enclosure.	\$27,737.00
PE-HB-AC-57P/L	57" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 8,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/8 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$10,236.00
Model #	Ultra Bright LCD Monitor- 57"	List
UB-N5720	SunView 57" Ultrabright LCD. 2500 NITS maximum light output 57" diagonal viewable area, 1800:1 contrast ratio, 1920 x 1080 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 220V/12A only. Day light viewable 57" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), DVI-D. Requires PE-UB- AC-Enclosure.	\$30,785.00
PE-UB-AC-57P/L	57" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 12,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/12 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$10,700.00
Model #	Options for 57" High Bright / Ultra Bright LCD Monitor	List
OPT-OTS-57	Touchscreen for 57" Panel Enclosure - Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 7 year or 60 Million actuations life, 92%-100% transmission accuracy, no drift, vandal proof.	\$4,500.00
PE-Ped-57-P/L	Pedestal for PE-AC-57 with base - same dimensional as enclosure accessories to your specification. Heavy gauge steel construction, access door, floor base. Specify required height. Complies with ADA Requirements.	\$593.00

OPT-Heat	Heating Sub System Provides heating to any PE and PE-AC Panel Enclosure. Designed to elevate interior temperature up to panel's proper operating range. Extends lower temp range to sub-zero.	\$743.00
Model #	High Bright LCD Monitor- 65"	List
HB-N6520	SunView 65" Highbright LCD. 1500 NITS maximum light output 65" diagonal viewable area, 2,000:1 contrast ratio, 1920 x 1080 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 220V/10A only. Day light viewable 65" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), HDMI. Requires PE-UB-AC- Enclosure.	\$30,068.00
PE-HB-AC-65P/L	65" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 10,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/10 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$10,750.00
Model #	Ultra Bright LCD Monitor- 65"	List
UB-N6520	SunView 65" Ultrabright LCD. 2500 NITS maximum light output 65" diagonal viewable area, 2,000:1 contrast ratio, 1920 x 1080 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 220V/16A only. Day light viewable 65" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), HDMI. Requires PE-UB-AC- Enclosure.	\$35,976.00
PE-UB-AC-65P/L	65" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 15,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/15 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$11,415.00

Model #	Options for 65" High Bright / Ultra Bright LCD Monitor	List
OPT-OTS-65	Touchscreen for 65" Panel Enclosure - Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 7 year or 60 Million actuations life, 92%-100% transmission accuracy, no drift, vandal proof.	\$5,642.00
PE-Ped-65-P/L	Pedestal for PE-AC-65 with base - same dimensional as enclosure accessories to your specification. Heavy gauge steel construction, access door, floor base. Specify required height. Complies with ADA Requirements.	\$680.00
OPT-Heat	Heating Sub System Provides heating to any PE and PE-AC Panel Enclosure. Designed to elevate interior temperature up to panel's proper operating range. Extends lower temp range to sub-zero.	\$743.00
Model #	High Bright LCD Monitor- 70"	List
HB-N7020	SunView 70" Highbright LCD. 1500 NITS maximum light output 70" diagonal viewable area, 2,000:1 contrast ratio, 1920 x 1080 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 220V/12A only. Day light viewable 70" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), HDMI. Requires PE-UB-AC- Enclosure.	\$36,908.00
PE-HB-AC-70P/L	70" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 12,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/12 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$11,579.00
Model #	Ultra Bright LCD Monitor- 70"	List
UB-N7020	SunView 70" Ultrabright LCD. 2500 NITS maximum light output 70" diagonal viewable area, 2,000:1 contrast ratio, 1920 x 1080 resolution, 16:9 aspect ratio, LED backlight life 50,000 hours at 50% brightness, 220V/19A only. Day light viewable 70" monitor with auto dimming capability. Inputs: RGBHV (5BNC), VGA (15 pin HD), HDMI. Requires PE-UB-AC- Enclosure.	\$43,997.00

PE-UB-AC-70P/L	70" Outdoor Panel Enclosure: All-metal, NEMA3R weatherproof enclosure. Hinged door with tamper resistant lock system, 1/2" abrasion-resistant, polycarbonate window. Hinged door with tamper resistant lock system. Integrated 18,000 BTU Air Conditioner with programmable, digital thermostat and circulation fans. RS-232 I/O for remote monitoring and control. Internal mount for 1 RU EIA accessory. 110V/18 amps. Ambient temperature range 35°-110° F. Specify Portrait or Landscape mode.	\$12,129.00
Model #	Options for 70" High Bright / Ultra Bright LCD Monitor	List
OPT-OTS-70	Touchscreen for 70" Panel Enclosure - Sealed, splashproof Infrared technology. 4096 x 4096 touch resolution, 7 year or 60 Million actuations life, 92%-100% transmission accuracy, no drift, vandal proof.	\$6,350.00
PE-Ped-70-P/L	Pedestal for PE-AC-70 with base - same dimensional as enclosure accessories to your specification. Heavy gauge steel construction, access door, floor base. Specify required height. Complies with ADA Requirements.	\$707.00
OPT-Heat	Heating Sub System Provides heating to any PE and PE-AC Panel Enclosure. Designed to elevate interior temperature up to panel's proper operating range. Extends lower temp range to sub-zero.	\$743.00

Wall Plates & Rack Panels		
Model #	Blank Rack Panels & Accessories	List
IDP-1	1 RU Dealer ID Panel Black vinyl face with Dealer Logo as white text. Dealer must supply logo.	\$48.50
BP-1	1 RU Blank Black textured powder coat, flanged steel	\$10.50
BP-2	2 RU Blank Black textured powder coat, flanged steel	\$12.50
BP-3	3 RU Blank Black textured powder coat, flanged steel	\$14.50
BP-4	4 RU Blank Black textured powder coat, flanged steel	\$16.50
ABP-1	1 RU Blank Brushed black anodized	\$15.50
ABP-2	2 RU Blank Brushed black anodized	\$17.50
ABP-3	3 RU Blank Brushed black anodized	\$20.50
ABP-4	4 RU Blank Brushed black anodized	\$23.50
ABP-5	5 RU Blank Brushed black anodized	\$24.00
RLR	Rack Lace Bars Black Zinc finish - 10 per pack	\$40.00
CUSTOM	Custom Rack Panels to your specifications - download checklist from website	Quote
L-Kit / Com	Label Kit / Commercial Self adhesive label of 40 common connector designations.	\$15.00
L-Kit / Res	Label Kit / Residential Self adhesive label of 40 common connector designations.	\$15.00
Model #	Custom Wall Plates & Rack Panels	List
PP-1RU-08	Prepunched 1RU EIA Panel with 8 Neutrik D series punches. Select from connectors listed below.	\$22.00
PP-2RU-16	Prepunched 2RU EIA Panel with 16 Neutrik D series punches. Select from connectors listed below.	\$24.00
PP-1G-02	Prepunched Single Gang Plate with 2 Neutrik D series punches. Select from connectors listed below.	\$18.00
PP-2G-04	Prepunched Double Gang Plate with 4 Neutrik D series punches. Select from connectors listed below.	\$22.00
4001-00050	BNC Pass thru Neutrik D series (red)	\$7.00
4001-00060	BNC Pass thru Neutrik D series (green)	\$7.00
4001-00070	BNC Pass thru Neutrik D series (blue)	\$7.00
4001-00080	BNC Pass thru Neutrik D series (yellow)	\$7.00
4001-00090	BNC Pass thru Neutrik D series (black)	\$7.00
4001-00110	3pin XLR Female solder back Neutrik D series	\$4.25
4001-00120	3pin XLR Male solder back Neutrik D series	\$5.25
4001-00130	4pin XLR Female solder back Neutrik D series	\$10.90
4001-00140	4pin XLR Male solder back Neutrik D series	\$7.25
4001-00150	1/4" Phone mono or stereo solder back Neutrik D series	\$10.40
4001-00160	RCA Female pass thru Neutrik D series (red)	\$5.30
4001-00170	RCA Female pass thru Neutrik D series (green)	\$5.30
4001-00180	RCA Female pass thru Neutrik D series (blue)	\$5.30
4001-00190	RCA Female pass thru Neutrik D series (yellow)	\$5.30
4001-00200	RCA Female pass thru Neutrik D series (black)	\$5.30

4001-00220	S-VHS Video pass thru Neutrik D series	\$19.25
4001-00230	PS/2 pass thru 6 pin connector Neutrik D series	\$13.90
4001-00240	RJ-45 pass thru Neutrik D series	\$16.00
4001-00250	Blank Cover for unused D series Prepunched	\$1.25
L-Kit / Com	Label Kit / Commercial Self adhesive label of 40 common commercial connector designations.	\$15.00
L-Kit / Res	Label Kit / Residential Self adhesive label of 40 common residential connector designations.	\$15.00
Model #	Stock Wall Plates	List
10-03-S	Single Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors	\$24.75
10-03-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors	\$24.75
10-03-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors	\$24.75
10-53-S	Single Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors	\$74.50
10-53-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors	\$74.50
10-53-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors	\$74.50
10-04-S	Single Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) BNC pass-thru and 2) RCA solder-back connectors	\$19.25
10-04-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) BNC pass-thru and 2) RCA solder-back connectors	\$19.25
10-04-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1) BNC pass-thru and 2) RCA solder-back connectors	\$19.25
10-05-S	Single Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) BNC pass-thru, 2) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$34.50
10-05-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) BNC pass-thru, 2) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$34.50

10-05-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1) BNC pass-thru, 2) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$34.50
10-55-S	Single Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) BNC pass-thru, 2) RCA solder-back, 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$81.95
10-55-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) BNC pass-thru, 2) RCA solder-back, 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$81.95
10-55-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1) BNC pass-thru, 2) RCA solder-back, 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$81.95
10-07-S	Single Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) RCA pass-thru, 2) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$34.50
10-07-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) RCA pass-thru, 2) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$34.50
10-07-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1) RCA pass-thru, 2) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$34.50
10-57-S	Single Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) RCA pass-thru, 2) RCA solder-back, 1) DDI HD-15p VGA BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$81.95
10-57-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) RCA pass-thru, 2) RCA solder-back, 1) DDI HD-15p VGA BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$81.95
10-57-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1) RCA pass-thru, 2) RCA solder-back, 1) DDI HD-15p VGA BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$81.95
10-08-S	Single Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) S-VHS pass-thru, 2) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$47.00
10-08-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) S-VHS pass-thru, 2) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$47.00

10-08-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1) S-VHS pass-thru, 2) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$47.00
10-58-S	Single Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) S-VHS pass-thru, 2) RCA solder-back, 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$96.60
10-58-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) S-VHS pass-thru, 2) RCA solder-back, 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$96.60
10-58-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1) S-VHS pass-thru, 2) RCA solder-back, 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$96.60
20-03-S	Double Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) BNC pass-thru, 2) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$34.95
20-03-W	Double Gang Wall Plate , White Steel w/ black text. Includes 1) BNC pass-thru, 2) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$34.95
20-03-B	Double Gang Wall Plate , Black Steel w/ white text. Includes 1) BNC pass-thru, 2) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$34.95
20-53-S	Double Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) BNC pass-thru, 2) RCA solder-back, 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$84.50
20-53-W	Double Gang Wall Plate , White Steel w/ black text. Includes 1) BNC pass-thru, 2) RCA solder-back, 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$84.50
20-53-B	Double Gang Wall Plate , Black Steel w/ white text. Includes 1) BNC pass-thru, 2) RCA solder-back, 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$84.50
20-04-S	Double Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 6) BNC pass-thru, 1) 3.5mm mini stereo solder-back and 2) RCA solder-back connectors	\$46.95
20-04-W	Double Gang Wall Plate , White Steel w/ black text. Includes 6) BNC pass-thru, 1) 3.5mm mini stereo solder-back and 2) RCA solder-back connectors	\$46.95

20-04-B	Double Gang Wall Plate , Black Steel w/ white text. Includes 6) BNC pass-thru, 1) 3.5mm mini stereo solder-back and 2) RCA solder-back connectors	\$46.95
20-05-S	Double Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) BNC pass-thru, 1) S-Video solder-back, 4) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$55.50
20-05-W	Double Gang Wall Plate , White Steel w/ black text. Includes 1) BNC pass-thru, 1) S-Video solder-back, 4) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$55.50
20-05-B	Double Gang Wall Plate , Black Steel w/ white text. Includes 1) BNC pass-thru, 1) S-Video solder-back, 4) RCA solder-back, 1) HD-15p VGA pass-thru and 1) 3.5mm mini stereo solder-back connectors.	\$55.50
20-55-S	Double Gang Wall Plate , Brushed Stainless Steel w/ black text. Includes 1) BNC pass-thru, 1) S-Video solder-back, 4) RCA solder-back, 1) HD-15p VGA BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$105.00
20-55-W	Double Gang Wall Plate , White Steel w/ black text. Includes 1) BNC pass-thru, 1) S-Video solder-back, 4) RCA solder-back, 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$105.00
20-55-B	Double Gang Wall Plate , Black Steel w/ white text. Includes 1) BNC pass-thru, 1) S-Video solder-back, 4) RCA solder-back, 1) DDI HD-15p BreakThrough and 1) 3.5mm mini stereo solder-back connectors.	\$105.00
10-21-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1 pair) Gold speaker Binding Posts for up to 5 AWG or banana plug.	\$45.00
10-21-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1 pair) Gold solder-back speaker Binding Posts for up to 5 AWG or banana plug.	\$45.00
10-22-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) Gold S-Video pass-thru and 3) Gold RCA pass-thru connectors.	\$50.60
10-22-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1) Gold S-Video pass-thru and 3) Gold RCA pass-thru connectors.	\$50.60
10-23-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) DDI S-Video BreakThrough and 3) Gold RCA pass-thru connectors.	\$61.80
10-23-B	Single Gang Wall Plate , White Steel w/ black text. Includes 1) DDI S-Video BreakThrough and 3) Gold RCA pass-thru connectors.	\$61.80
10-24-W	Single Gang Wall Plate , White Steel w/ black text. Includes 3) Gold RCA pass-thru connectors.	\$32.50

10-24-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 3) Gold RCA pass-thru connectors.	\$32.50
20-25-W	Double Gang Wall Plate , White Steel w/ black text. Includes 1) Gold RCA pass-thru connector and 5 pair) Gold solder-back speaker Binding Posts for up to 5 AWG or banana plug.	\$125.50
20-25-B	Double Gang Wall Plate , Black Steel w/ white text. Includes 1) Gold RCA pass-thru connector and 5 pair) Gold solder-back speaker Binding Posts for up to 5 AWG or banana plug.	\$125.50
10-26-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) RF pass-thru and 1) RJ-11 connectors.	\$30.00
10-26-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1) RF pass-thru and 1) RJ-11 connectors.	\$30.00
10-27-W	Single Gang Wall Plate , White Steel w/ black text. Includes 1) Gold RCA pass-thru connector.	\$28.00
10-27-B	Single Gang Wall Plate , Black Steel w/ white text. Includes 1) Gold RCA pass-thru connector.	\$28.00
CP-001	C-Port Retaining plate for VGA cable - for installation in lectern or table. For easy access to interconnect laptop computer	\$60.00
CC-BNC5	Color Coded BNC Isolators Specify color: Red, Green, Blue, White, Yellow, Black - packs of 50 washers	\$7.50
CUSTOM	Custom Wall Plates to your specifications - download checklist from www.displaydevices.com	Quote

Model #	Wolfvision Products	List
WV-BX-TEMP	Plenum Temperature Box w/ mount for Wolfvision VZ-(C11-32). Rigid mounting for Visualizer within temperature controlled plenum housing above 2' X 2' drop tile ceiling. Intake and exhaust fans for cooling. UL rated fire dampers to maintain plenum rating. Includes optical glass projection port. 110 VAC. Includes PCM-WV-C quick release mount. Black powder coat finish.	\$1,395.00
PCM-WV-C	Ceiling Mount for WolfVision Visualizer VZ-(C11- 32), 20° tilt, 10° pitch, 180° yaw with 250 Lb weight capacity and 2 inch threaded flange.	\$215.00
BX-VIT	Vibration Isolation Kit. To control vibration in WV-BX-TEMP Plenum Enclosure installations. Mount plate with vibration isolators interfaces between Visualizer mount and enclosure.	\$115.00
WV-PORT	Ceiling Tile Projection Port. Attaches to cut-out section of ceiling tile. Used in non-plenum, above-ceiling installations. Powder coat white finish.	\$106.00