



Camera and lens not included.

The PT-50 is ideal for distance learning, worship facilities and city council broadcasting applications in light-duty, indoor environments.

- Can link more than 99 total devices on one RS485 control chain
- Smooth pan and tilt action with accurate performance
- Designed for small camera/lens combinations
- Optional Camera Control Module for select cameras
- Small, unobtrusive, ultra-quiet design
- Up to 64 presets per head stored internally in non-volatile memory
- Control software available for Windows NT/2000/XP compatible PCs
- Control of either direct drive or servo drive lenses
- Integrated camera power supply
- All required connectors for power and control included
- 5-pin power and control connector eliminates need for soldering
- Video and Genlock signal routed through Pan/Tilt base
- Composite pass thru, optional component or SDI out

FEATURES & BENEFITS

DRAWINGS & SPECIFICATIONS

- Weight Capacity: 6 lbs. (2.7 kg.)
- Pan Range: +/- 179°;
- Tilt Range: +/- 45°
- Speed: Variable 0-25° per second
- Accuracy: +/- 5 arc minutes (.08°)
- Control: RS-485 / RS-232 Switchable
- Presets: 64 Maximum (20 w/ VXC-50)
- Power: 24 VDC
- Current: 1.5 amp / 2.5 amp with camera
- Weight: 8 lbs. (3.6 kg)
- Built in 12 VDC camera power supply
- Pedestal- or Ceiling-configurable
- Requires Telecon or DC drive lens
- 1 year warranty

List Price \$2,660

